

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Name : AMPRO Seal Resin
Type of product : Epoxy resin
Product group : Resin

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Intended for general public
Main use category : Professional use, Consumer use, Industrial use
Industrial/Professional use spec : None
For professional use only

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Gurit (UK) Ltd
St Cross Business Park
Newport
PO30 5WU Isle of Wight - United Kingdom
T +44 (0) 1983 828 000 (All Technical and Commercial Enquiries)
Regulatory@gurit.com - www.gurit.com

1.4. Emergency telephone number

Emergency number : Carechem 24: +44 (0) 1273 289451 24 Hours
Telephone number for use in case of chemical exposure, spillage or fire only.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Skin corrosion/irritation, Category 1, Sub-Category 1C H314
Serious eye damage/eye irritation, Category 1 H318
Skin sensitisation, Category 1 H317
Hazardous to the aquatic environment — Chronic Hazard, Category 2 H411
Full text of H statements : see section 16

Adverse physicochemical, human health and environmental effects

Causes severe skin burns and eye damage. May cause an allergic skin reaction. Causes serious eye damage. Toxic to aquatic life with long lasting effects.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS05

GHS07

GHS09

Signal word (CLP) :

Danger

Hazardous ingredients :

oxirane, mono[(C12-14-alkyloxy)methyl] derivs.; Benzenesulfonicacid,4-methyl-,methylester; Formaldehyde, polymer with 2-(chloromethyl)oxirane and phenol; bis-[4-(2,3-epoxypropoxy)phenyl]propane; 1,4-bis(2,3 epoxypropoxy)butane; butanedioldiglycidyl ether

AMPRO Seal Resin

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Hazard statements (CLP)	: H314 - Causes severe skin burns and eye damage. H317 - May cause an allergic skin reaction. H411 - Toxic to aquatic life with long lasting effects.
Precautionary statements (CLP)	: P102 - Keep out of reach of children. P260 - Do not breathe vapours. P264 - Wash hands thoroughly after handling. P272 - Contaminated work clothing should not be allowed out of the workplace. P273 - Avoid release to the environment. P280 - Wear eye protection, protective clothing, protective gloves.

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
bis-[4-(2,3-epoxypropoxy)phenyl]propane	(CAS-No.) 1675-54-3 (EC-No.) 216-823-5 (EC Index-No.) 603-073-00-2 (REACH-no) 01-2119456619-26	≥ 25	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 2, H411
oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	(CAS-No.) 68609-97-2 (EC-No.) 271-846-8 (EC Index-No.) 603-103-00-4 (REACH-no) 01-2119485289-22	25 – 50	Skin Irrit. 2, H315 Skin Sens. 1, H317
Formaldehyde, polymer with 2-(chloromethyl)oxirane and phenol	(CAS-No.) 9003-36-5 (EC-No.) 500-006-8 (REACH-no) 01-2119454392-40	5 – 25	Skin Irrit. 2, H315 Skin Sens. 1, H317 Aquatic Acute Not classified Aquatic Chronic 2, H411
1,4-bis(2,3 epoxypropoxy)butane; butanedioldiglycidyl ether	(CAS-No.) 2425-79-8 (EC-No.) 219-371-7 (EC Index-No.) 603-072-00-7 (REACH-no) 01-2119494060-45	5 – 10	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Acute Tox. 4 (Inhalation:vapour), H332 Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Chronic 3, H412
Benzenesulfonicacid,4-methyl-,methylester	(CAS-No.) 80-48-8 (EC-No.) 201-283-5	1 – 10	Acute Tox. 4 (Oral), H302 Skin Corr. 1C, H314 Eye Dam. 1, H318 Skin Sens. 1B, H317

Specific concentration limits:

Name	Product identifier	Specific concentration limits
bis-[4-(2,3-epoxypropoxy)phenyl]propane	(CAS-No.) 1675-54-3 (EC-No.) 216-823-5 (EC Index-No.) 603-073-00-2 (REACH-no) 01-2119456619-26	(5 ≤C < 100) Skin Irrit. 2, H315 (5 ≤C < 100) Eye Irrit. 2, H319

Full text of H-statements: see section 16

AMPRO Seal Resin

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: Call a physician immediately.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Rinse skin with water/shower. Take off immediately all contaminated clothing. Call a physician immediately.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician immediately.
First-aid measures after ingestion	: Rinse mouth. Do not induce vomiting. Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after skin contact	: Burns. May cause an allergic skin reaction.
Symptoms/effects after eye contact	: Serious damage to eyes.
Symptoms/effects after ingestion	: Burns.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media	: Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products in case of fire	: Toxic fumes may be released.
--	--------------------------------

5.3. Advice for firefighters

Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
Other information	: Collect contaminated fire fighting water separately. It must not enter drains.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures	: Ventilate spillage area. Avoid contact with skin and eyes. Do not breathe vapours.
----------------------	--

6.1.2. For emergency responders

Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
Emergency procedures	: Ventilate area.

6.2. Environmental precautions

Avoid release to the environment. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

For containment	: Collect spillage.
Methods for cleaning up	: Take up liquid spill into absorbent material.
Other information	: Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13. For further information refer to section 8: "Exposure controls/personal protection".

AMPRO Seal Resin

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Ensure good ventilation of the work station. Avoid contact with skin and eyes. Do not breathe vapours. Wear personal protective equipment.
- Hygiene measures : Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Separate working clothes from town clothes. Launder separately. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Store locked up. Store in a well-ventilated place. Keep cool.
- Maximum storage period : 2 year
- Storage temperature : ≤ 30 °C Storage at elevated temperatures may cause pressure build-up in sealed containers
- Storage area : Store away from heat. Store in a well-ventilated place.
- Special rules on packaging : Keep only in original container.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

No additional information available

8.2. Exposure controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

Hand protection:

Protective gloves

Type	Material	Permeation	Thickness (mm)	Penetration	Standard
Disposable gloves	Nitrile rubber (NBR)				EN ISO 374

Eye protection:

Safety glasses

Skin and body protection:

Wear suitable protective clothing

Type	Standard
Tyvek® Gown/Coveralls	EN 13034

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment. Where exposure through inhalation may occur from use, respiratory protection equipment is recommended

Device	Filter type	Condition	Standard
Disposable half mask	Gas/vapour filter	Vapour protection	EN 405

AMPRO Seal Resin

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Personal protective equipment symbol(s):



Environmental exposure controls:

Avoid release to the environment.

Other information:

Industrial and professional. Perform risk assessment prior to use. Do not eat, drink or smoke when using this product.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Clear, colorless liquid.
Colour	: clear.
Odour	: characteristic.
Odour threshold	: No data available
pH	: ≈ 5
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: No data available
Flash point	: > 200 °C Estimated on the basis of the constituents :
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Not applicable
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Density	: 1.09 g/cm ³ 21°C
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Viscosity, kinematic	: 105.505 mm ² /s
Viscosity, dynamic	: 115 cP 20°C
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport. Product is not explosive.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

AMPRO Seal Resin

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

oxirane, mono[(C12-14-alkyloxy)methyl] derivs. (68609-97-2)

LD50 oral rat	17100 mg/kg
LD50 oral	19200 mg/kg

1,4-bis(2,3 epoxypropoxy)butane; butanedioldiglycidyl ether (2425-79-8)

LD50 oral rat	1163 mg/kg
---------------	------------

Formaldehyde, polymer with 2-(chloromethyl)oxirane and phenol (9003-36-5)

LD50 oral rat	> 10000 mg/kg
LD50 dermal rat	> 2000 mg/kg

bis-[4-(2,3-epoxypropoxy)phenyl]propane (1675-54-3)

LD50 oral	1500 mg/kg bodyweight
LD50 dermal rat	23032 mg/kg bodyweight

Skin corrosion/irritation : Causes severe skin burns.
pH: ≈ 5
Serious eye damage/irritation : Causes serious eye damage.
pH: ≈ 5
Respiratory or skin sensitisation : May cause an allergic skin reaction.
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified

bis-[4-(2,3-epoxypropoxy)phenyl]propane (1675-54-3)

IARC group	3 - Not classifiable
------------	----------------------

Reproductive toxicity : Not classified
STOT-single exposure : Not classified
STOT-repeated exposure : Not classified
Aspiration hazard : Not classified

AMPRO Seal Resin

Viscosity, kinematic	105.505 mm ² /s
----------------------	----------------------------

AMPRO Seal Resin

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	: Toxic to aquatic life with long lasting effects.
Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Toxic to aquatic life with long lasting effects.

Formaldehyde, polymer with 2-(chloromethyl)oxirane and phenol (9003-36-5)

LC50 fish 1	< 1 mg/l
-------------	----------

bis-[4-(2,3-epoxipropoxy)phenyl]propane (1675-54-3)

EC50 Daphnia 1	1.8 mg/l
EC50 Daphnia 2	0.3 mg/l (OECD 211 method)
EC50 72h algae (1)	11 mg/l

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

bis-[4-(2,3-epoxipropoxy)phenyl]propane (1675-54-3)

Partition coefficient n-octanol/water (Log Pow)	3.242
---	-------

12.4. Mobility in soil

bis-[4-(2,3-epoxipropoxy)phenyl]propane (1675-54-3)

Partition coefficient n-octanol/water (Log Koc)	2.65 (OECD 121 method)
---	------------------------

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Regional legislation (waste)	: Disposal must be done according to official regulations.
Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Product/Packaging disposal recommendations	: Avoid release to the environment. Dispose in a safe manner in accordance with local/national regulations.
Ecology - waste materials	: Avoid release to the environment.
European List of Waste (LoW) code	: 08 04 09* - waste adhesives and sealants containing organic solvents or other dangerous substances

SECTION 14: Transport information

In accordance with ADR / IATA / IMDG

AMPRO Seal Resin

Safety Data Sheet


according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

ADR	IMDG	IATA
14.1. UN number		
UN 1760	UN 1760	UN 1760
14.2. UN proper shipping name		
CORROSIVE LIQUID, N.O.S.	CORROSIVE LIQUID, N.O.S.	Corrosive liquid, n.o.s.
Transport document description		
UN 1760 CORROSIVE LIQUID, N.O.S. (Benzenesulfonicacid,4-methyl-,methylester ; Formaldehyde, polymer with (chloromethyl)oxirane and phenol), 8, III, (E), ENVIRONMENTALLY HAZARDOUS	UN 1760 CORROSIVE LIQUID, N.O.S. (Benzenesulfonicacid,4-methyl-,methylester ; Formaldehyde, polymer with (chloromethyl)oxirane and phenol), 8, III, MARINE POLLUTANT/ENVIRONMENTALLY HAZARDOUS	UN 1760 Corrosive liquid, n.o.s. (Benzenesulfonicacid,4-methyl-,methylester ; Formaldehyde, polymer with (chloromethyl)oxirane and phenol), 8, III, ENVIRONMENTALLY HAZARDOUS
14.3. Transport hazard class(es)		
8	8	8
14.4. Packing group		
III	III	III
14.5. Environmental hazards		
Dangerous for the environment : Yes	Dangerous for the environment : Yes Marine pollutant : Yes	Dangerous for the environment : Yes
No supplementary information available		

14.6. Special precautions for user

Overland transport

Classification code (ADR)	: C9
Special provisions (ADR)	: 274
Limited quantities (ADR)	: 5I
Excepted quantities (ADR)	: E1
Packing instructions (ADR)	: P001, IBC03, LP01, R001
Mixed packing provisions (ADR)	: MP19
Portable tank and bulk container instructions (ADR)	: T7
Portable tank and bulk container special provisions (ADR)	: TP1, TP28
Tank code (ADR)	: L4BN
Vehicle for tank carriage	: AT
Transport category (ADR)	: 3
Special provisions for carriage - Packages (ADR)	: V12
Hazard identification number (Kemler No.)	: 80
Orange plates	:



Tunnel restriction code (ADR)	: E
EAC code	: 2X
APP code	: B

AMPRO Seal Resin

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Transport by sea

Special provisions (IMDG)	: 223, 274
Packing instructions (IMDG)	: P001, LP01
IBC packing instructions (IMDG)	: IBC03
Tank instructions (IMDG)	: T7
Tank special provisions (IMDG)	: TP1, TP28
EmS-No. (Fire)	: F-A
EmS-No. (Spillage)	: S-B
Stowage category (IMDG)	: A
Stowage and handling (IMDG)	: SW2
Properties and observations (IMDG)	: Causes burns to skin, eyes and mucous membranes.

Air transport

PCA Excepted quantities (IATA)	: E1
PCA Limited quantities (IATA)	: Y841
PCA limited quantity max net quantity (IATA)	: 1L
PCA packing instructions (IATA)	: 852
PCA max net quantity (IATA)	: 5L
CAO packing instructions (IATA)	: 856
CAO max net quantity (IATA)	: 60L
Special provisions (IATA)	: A3, A803
ERG code (IATA)	: 8L

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Full text of H- and EUH-statements:

Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Inhalation:vapour)	Acute toxicity (inhalation:vapour) Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Acute Not classified	Hazardous to the aquatic environment - Acute Hazard Not classified
Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment — Chronic Hazard, Category 3
Eye Dam. 1	Serious eye damage/eye irritation, Category 1

AMPRO Seal Resin

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Skin Corr. 1C	Skin corrosion/irritation, Category 1, Sub-Category 1C
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
Skin Sens. 1B	Skin sensitisation, category 1B
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Skin Corr. 1C	H314	Calculation method
Eye Dam. 1	H318	Calculation method
Skin Sens. 1	H317	Calculation method
Aquatic Chronic 2	H411	Calculation method

SDS EU (REACH Annex II)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product. The information contained within this document is Gurit copyright and any distribution or publication beyond the recipient's organisation is prohibited without Gurit's prior written consent.