

# U-POL™

## SAFETY DATA SHEET

UPOL BODYFILLER RANGE

Page 1

Issued: 02/07/2008

Revision No: 4

### 1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING

**Product name:** UPOL BODYFILLER RANGE

**Product code:** VARIOUS

**Synonyms:** P38, P40, FIBRAL, QUICSAND, DOLPHIN, EASY, MONARCH, EASYLITE, EXTRA, EXTRA GOLD, FANTASTIC, HOTSHOT, GALVX, SMC, TOPSTOP, FLYWEIGHT, TOPSTOP GOLD, UPOLB, UPOLC, UPOLD, UPOLE.

**Use of substance / preparation:** POLYESTER REPAIR PASTE CONTAINING STYRENE

Classified as Hazardous according to criteria of NOHSC

**Company name:** U-POL Australia PTY Ltd.

Unit A,

16 - 20 Cassola Place

Penrith

NSW 2777

Australia

Tel: 02 4731 2655

Fax: 02 4731 2611

Emergency tel: 0418 726 984

Email: technical@u-pol.com

### 2. HAZARDS IDENTIFICATION

**Main hazards:** Flammable. Harmful by inhalation. Irritating to eyes and skin.

**Other hazards:** Flammable. Harmful by inhalation. Irritating to eyes. Irritating to skin.

### 3. COMPOSITION / INFORMATION ON INGREDIENTS

**Hazardous ingredients:** STYRENE 10-30%

EINECS: 202-851-5 CAS: 100-42-5

[-] R10; [Xn] R20; [Xi] R36/38

### 4. FIRST AID MEASURES (SYMPTOMS)

**Skin contact:** There may be irritation and redness at the site of contact.

**Eye contact:** There may be irritation and redness.

[cont...]

# SAFETY DATA SHEET

UPOL BODYFILLER RANGE

**Ingestion:** Nausea and stomach pain may occur.

**Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest.

## 4. FIRST AID MEASURES (ACTION)

**Skin contact:** Wash immediately with plenty of soap and water.

**Eye contact:** Bathe the eye with running water for 15 minutes. Consult a doctor.

**Ingestion:** Do not induce vomiting. Wash out mouth with water. Consult a doctor.

**Inhalation:** Remove casualty from exposure ensuring one's own safety whilst doing so.

## 5. FIRE-FIGHTING MEASURES

**Extinguishing media:** Carbon dioxide. Dry chemical powder. Alcohol or polymer foam.

**Exposure hazards:** Flammable. In combustion emits toxic fumes of carbon dioxide / carbon monoxide.

**Protection of fire-fighters:** Wear protective clothing to prevent contact with skin and eyes.

## 6. ACCIDENTAL RELEASE MEASURES

**Personal precautions:** Refer to section 8 of SDS for personal protection details.

**Environmental precautions:** Do not discharge into drains or rivers. Contain the spillage using bunding.

**Clean-up procedures:** Absorb into dry earth or sand.

## 7. HANDLING AND STORAGE

**Handling requirements:** Ensure there is sufficient ventilation of the area.

**Storage conditions:** Store in cool, well ventilated area. Keep away from sources of ignition. Keep container tightly closed.

**Suitable packaging:** Must only be kept in original packaging.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

### Workplace exposure limits

**WEL (8 hr TWA):** 100 ppm

**WEL (15 min STEL):** 250 ppm

### Respirable dust

**WEL (8 hr TWA):** 1 mg/m<sup>3</sup>

**Hazardous ingredients:** STYRENE

WEL (8 hr TWA): 430 mg/m<sup>3</sup> WEL (15 min STEL): 1080 mg/m<sup>3</sup>

**Engineering measures:** Ensure there is sufficient ventilation of the area.

**Respiratory protection:** Respiratory protective device with particle filter.

**Hand protection:** Nitrile gloves.

**Eye protection:** Safety glasses with side-shields.

**Skin protection:** Protective clothing.

**9. PHYSICAL AND CHEMICAL PROPERTIES****State:** Paste**Odour:** Aromatic**Evaporation rate:** Slow**Solubility in water:** Insoluble**Also soluble in:** Most organic solvents.**Viscosity:** Highly viscous**Viscosity value:** 500,000 CP**Flammability limits %: lower:** 1.1**upper:** 6.1**Flash point°C:** 32**Autoflammability°C:** 490**Relative density:** 1.5**VOC g/l:** 300**10. STABILITY AND REACTIVITY****Stability:** Stable under normal conditions.**Conditions to avoid:** Direct sunlight. Heat. Sources of ignition.**Materials to avoid:** Oxidising agents.**Haz. decomp. products:** In combustion emits toxic fumes of carbon dioxide / carbon monoxide.**11. TOXICOLOGICAL INFORMATION****Hazardous ingredients:** STYRENE

IVN MUS LD50 90 mg/kg

ORL MUS LD50 316 mg/kg

ORL RAT LD50 2650 mg/kg

**Routes of exposure:** Refer to section 4 of SDS for routes of exposure and corresponding symptoms.**12. ECOLOGICAL INFORMATION****Mobility:** Insoluble in water. Heavier than water.**Persistence and degradability:** Not biodegradable.**Bioaccumulative potential:** No data available.**Other adverse effects:** Harmful to aquatic organisms.**13. DISPOSAL CONSIDERATIONS****Disposal operations:** D1 Tipping above or underground (e.g. landfill, etc.).**Disposal of packaging:** Dispose of in a regulated landfill site or other method for hazardous or toxic wastes.**NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

**SAFETY DATA SHEET**

UPOL BODYFILLER RANGE

**14. TRANSPORT INFORMATION****ADR / RID**

**UN no:** 3269 **ADR Class:** 3  
**Packing group:** III **Classification code:** F1  
**Shipping name:** POLYESTER RESIN KIT  
**Labelling:** 3

**IMDG / IMO**

**UN no:** 3269 **Class:** 3  
**Packing group:** III **EmS:** F-E,S-D  
**Marine pollutant:** .  
**Labelling:** 3

**IATA / ICAO**

**UN no:** 3269 **Class:** 3  
**Packing group:** III  
**Packing instructions:** 312  
**Labelling:** 3

**15. REGULATORY INFORMATION**

**Hazard symbols:** Harmful.



**Risk phrases:** R10: Flammable.  
R20: Harmful by inhalation.  
R36/38: Irritating to eyes and skin.

**Safety phrases:** S2: Keep out of the reach of children.  
S3: Keep in a cool place.  
S46: If swallowed, seek medical advice immediately and show this container or label.  
S51: Use only in well-ventilated areas.  
STYRENE

**Note:** The regulatory information given above only indicates the principal regulations specifically applicable to the product described in the safety data sheet. The user's attention is drawn to

**SAFETY DATA SHEET**

UPOL BODYFILLER RANGE

the possible existence of additional provisions which complete these regulations. Refer to all applicable national, international and local regulations or provisions.

US VOC CONVERSION FACTOR 250 g/l = 2.1 lb/gal

**16. OTHER INFORMATION**

**Other information:** This safety data sheet is prepared in accordance with Regulation (EC) No 1907/2006.

FOR PROFESSIONAL USE ONLY. Read full instructions before use.

IMPORTANT: This product contains hazardous materials and therefore appropriate personal protective equipment should always be used.

Please refer to the label and consult the material safety data sheet for full handling instructions and personal protection information. These are available via your local stockist or via the U-POL website at [WWW.U-POL.COM](http://WWW.U-POL.COM).

U-POL disclaim any liability where the user does not wear the recommended personal protective equipment.

**Risk phrases used in s.3:** R10: Flammable.

R20: Harmful by inhalation.

R36/38: Irritating to eyes and skin.

**Legal disclaimer:** The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. Addition of reducers, hardeners and other additives over and above U-POL's recommendations for use, may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, this company shall not be held liable for any damage resulting from handling or from contact with the above product.