

# PRODUCT DATA SHEET FOR # 1000L or 1000L-AS: HI-LOW LIQUID WAX or ANTI-STATIC LW

#### PRODUCT DESCRIPTION

# 1000L-AS, Hi-Low Anti Static Liquid Wax offers you the utmost in mold release factors either with accelerated heat (exotherm), low heat or room temperature. It is a blend of synthetic waxes and polymers which are not subject to the quality fluctuations so often found in natural waxes, depending upon their origin. In our formula, we feel the most important features of these synthetics are their high melting points and great hardness. Because of these features, and other desirable properties the resulting film upon proper application has high gloss, intensive wear and great resistance to heat and water.

Due to anti-stat properties it eliminates dust and particle attraction to mold due to static electricity buildup. Keeps molds in production with greater productivity, reduced costs and for the better bottom line and increased profits.

#### **APPLICATION**

Once mold is properly broken in by using FK's # 1000P, Hi-Low Paste Wax, we recommend using FK's liquid wax system, # 1000L-AS, Anti- Static Hi-Low Liquid Wax.

Apply 2-3 coats. Spread evenly, agitate lightly, allow it to dry and wipe.

This product contains sufficient waxes to continue easy demolding and multiple releases and it reactivates and spreads the paste wax deterring any possible wax build up or surface tension.

Continue to intermittently use 1000P and 1000L. This will extend use of the mold and will deter the problem of wax build up and most important surface tension.

## TYPICAL PHYSICAL CHARACTERISTICS

Weight: 7.00 Pounds per gallon

Color: Yellow (Liquid)
Flash Point: 112° F (TCC Method)

Shelf life: 1 year from date of shipment

### FINISH KARE'S LIMITATIONS OF LIABILITY

To the best of our knowledge, the data presented here is true and accurate, but is subject to change without prior notice. User is kindly requested to contact Finish Kare Products to verify the correctness before specifying or ordering. Since we don't know how the product will be used we cannot assume any responsibility for its use, performance, or any injuries resulting from its use. Liability, if any, is limited to replacement of defective product. NO WARRANTY OR GUARANTEE OF ANY KIND IS EXPRESSED OR IMPLIED BY FINISH KARE PRODUCTS, INC.

1726 Floradale Ave., South El Monte, CA 91733 Phone: 626-443-8983; Fax: 626-443-0288