# MBFibreglass mbfg.....

### SAFETY DATA SHEET

POLYCRAFT K2 PART B

Page: 1

Compilation date: 16/05/2016

**Revision date:** 16/05/2016

Revision No: 2

# Section 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product name: POLYCRAFT K2 PART B

Product code: K2 Part B

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: PC1: Adhesives, sealants. PC9a: Coatings and paints, thinners, paint removers. PC9b:

PROC1: Use in closed process, no likelihood of exposure PROC2: Use in closed, continuous process with occasional controlled exposure PROC3: Use in closed batch process (synthesis or formulation) PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises PROC5: Mixing or blending in batch processes for formulation of preparations\* and articles (multistage and/or significant contact) PROC8a:

Fillers, putties, plasters, modelling clay. PC32: Polymer preparations and compounds.

Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including

dipping and pouring PROC19: Hand-mixing with intimate contact and only PPE available ERC2: Formulation of preparations\* ERC3: Formulation in materials ERC5: Industrial use

resulting in inclusion into or onto a matrix ERC6d: Industrial use of process regulators for

weighing) PROC10: Roller application or brushing PROC13: Treatment of articles by

polymerisation processes in production of resins, rubbers, polymers

### 1.3. Details of the supplier of the safety data sheet

Company name: MB Fibreglass

Unit 17 & 20,

Abbey Business Park,

Mill Road,

Newtownabbey,

**BT36 7EE** 

Tel: 02890 861992

Email: sales@mbfg.co.uk

### POLYCRAFT K2 PART B

Page: 2

# 1.4. Emergency telephone number

Emergency tel: +44 (0) 2890 861992

(office hours only)

### **Section 2: Hazards identification**

### 2.1. Classification of the substance or mixture

Classification under CLP: Eye Irrit. 2: H319; Acute Tox. 4: H332; Carc. 2: H351; Resp. Sens. 1: H334; Skin Irrit. 2:

H315; Skin Sens. 1: H317; STOT RE 2: H373; STOT SE 3: H335

Most important adverse effects: Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation.

Harmful if inhaled. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause respiratory irritation. Suspected of causing cancer. May cause

damage to organs through prolonged or repeated exposure.

### 2.2. Label elements

Label elements:

Hazard statements: H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H319: Causes serious eye irritation.

H332: Harmful if inhaled.

H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335: May cause respiratory irritation. H351: Suspected of causing cancer.

H373: May cause damage to organs through prolonged or repeated exposure.

Hazard pictograms: GHS07: Exclamation mark

GHS08: Health hazard





Signal words: Danger

Precautionary statements: P260: Do not breathe dust/fumes/gas/mist/vapours/spray.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P302+352: IF ON SKIN: Wash with plenty of water/.

P304+340: IF INHALED: Remove person to fresh air and keep comfortable for breathing. P304+341: IF INHALED: If breathing is difficult, remove victim to fresh air and keep at

rest in a position comfortable for breathing.

P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

### 2.3. Other hazards

**PBT:** This product is not identified as a PBT/vPvB substance.

POLYCRAFT K2 PART B

Page: 3

# Section 3: Composition/information on ingredients

### 3.2. Mixtures

### Hazardous ingredients:

DIPHENYLMETHANE-4,4'-DI-ISOCYANATE - REACH registered number(s): 01-2119457014-47

EINECS	CAS	PBT / WEL	CLP Classification	Percent
202-966-0	101-68-8	-	Carc. 2: H351; Acute Tox. 4: H332; STOT RE 2: H373; Eye Irrit. 2: H319; STOT SE 3: H335; Skin Irrit. 2: H315; Resp. Sens. 1: H334; Skin Sens. 1: H317	>50%

METHYLENEDIPEHNYL DIISOCYANATE, DIPROPYLENEGLYCOL, TRIPROPYLENEGLYCOL COPOLYMER - REACH registered number(s): 01-2119492304-39

500-439-2	159168-82-8	-	Acute Tox. 4: H332; Skin Irrit. 2: H315;	25-50%
			Eye Irrit. 2: H319; Resp. Sens. 1:	
			H334; Carc. 2: H351; STOT RE 2:	
			H373; Skin Sens. 1: H317; STOT SE	
			3: H335	

### Section 4: First aid measures

# 4.1. Description of first aid measures

**Skin contact:** Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash

immediately with plenty of soap and water. Consult a doctor.

**Eye contact:** Bathe the eye with running water for 15 minutes. Consult a doctor.

**Ingestion:** Wash out mouth with water. Do not induce vomiting. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Move to

fresh air in case of accidental inhalation of vapours. If unconscious and breathing is OK,

place in the recovery position. Consult a doctor.

# 4.2. Most important symptoms and effects, both acute and delayed

**Skin contact:** There may be irritation and redness at the site of contact.

Eve contact: There may be irritation and redness.

Ingestion: Nausea and stomach pain may occur.

Inhalation: There may be a feeling of tightness in the chest with shortness of breath. Exposure may

cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

# 4.3. Indication of any immediate medical attention and special treatment needed

**Immediate / special treatment:** Show this safety data sheet to the doctor in attendance.

### Section 5: Fire-fighting measures

### POLYCRAFT K2 PART B

Page: 4

# 5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used.

# 5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes.

### 5.3. Advice for fire-fighters

**Advice for fire-fighters:** Wear protective clothing to prevent contact with skin and eyes. Wear self-contained breathing apparatus.

### Section 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

**Personal precautions:** Refer to section 8 of SDS for personal protection details. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of liquid.

### 6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

# 6.3. Methods and material for containment and cleaning up

Clean-up procedures: Mix with sand or vermiculite. Transfer to a closable, labelled salvage container for disposal by an appropriate method. Clean-up should be dealt with only by qualified personnel familiar with the specific substance.

### 6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS. Refer to section 13 of SDS.

# Section 7: Handling and storage

### 7.1. Precautions for safe handling

**Handling requirements:** Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area.

Do not handle in a confined space. Avoid the formation or spread of mists in the air.

### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Keep container tightly closed. Avoid contact with water or humidity. >20°C

Suitable packaging: Must only be kept in original packaging.

# 7.3. Specific end use(s)

Specific end use(s): No data available.

# Section 8: Exposure controls/personal protection

### 8.1. Control parameters

POLYCRAFT K2 PART B

Page: 5

# **Hazardous ingredients:**

# **DIPHENYLMETHANE-4,4'-DI-ISOCYANATE**

# Workplace exposure limits:

# Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	0.02 mg/m3	0.07 mg/m3	•	-

# **DNEL/PNEC Values**

# Hazardous ingredients:

# **DIPHENYLMETHANE-4,4'-DI-ISOCYANATE**

Туре	Exposure	Value	Population	Effect
DNEL	Inhalation	0.05 mg/m3	Workers	Systemic
DNEL	Inhalation	0.05 mg/m3	Workers	Local
PNEC	Fresh water	1 mg/l	-	-
PNEC	Marine water	0.1 mg/l	-	-
DNEL	Dermal	50 mg/kg bw/day	Workers	Systemic
DNEL	Inhalation	0.1 mg/m3 air	Workers	Systemic
DNEL	Dermal	28.7 mg/cm2	Workers	Local
DNEL	Inhalation	0.1 mg/m3 air	Workers	Local
DNEL	Inhalation (repeated dose)	0.05 mg/m3 air	Workers	Systemic
DNEL	Inhalation (repeated dose)	0.05 mg/m3 air	Workers	Local
DNEL	Dermal	25 mg/kg bw/day	General Population	Systemic
DNEL	Inhalation	0.05 mg/m3 air	General Population	Systemic
DNEL	Oral	20 mg/kg bw/day	General Population	Systemic
DNEL	Dermal	17.2 mg/cm2	General Population	Systemic
DNEL	Inhalation	0.05 mg/m3 air	General Population	Local
DNEL	Inhalation (repeated dose)	0.025 mg/m3 air	General Population	Systemic
DNEL	Inhalation (repeated dose)	0.025 mg/m3 air	General Population	Local
PNEC	Soil (agricultural)	> 1 mk dry weigt	-	-
PNEC	Microorganisms in sewage treatment	> 1 mg/l	•	-

# 8.2. Exposure controls

**Engineering measures:** Ensure there is sufficient ventilation of the area.

Respiratory protection: Gas/vapour filter, type A: organic vapours (EN141). Self-contained breathing apparatus

must be available in case of emergency.

Hand protection: Impermeable gloves.

Eye protection: Safety glasses. Ensure eye bath is to hand.

**Skin protection:** Impermeable protective clothing.

Environmental: Ensure all engineering measures mentioned in section 7 of SDS are in place.

### POLYCRAFT K2 PART B

Page: 6

upper: No data available.

Vapour pressure: No data available.

# Section 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

State: Liquid

Colour: Pale yellow

Odour: Barely perceptible odour

Evaporation rate: No data available.

Oxidising: No data available.

Solubility in water: Reacts with water.

Viscosity: 250 mPas (25°C)

Boiling point/range°C: No data available. Melting point/range°C: No data available.

Flammability limits %: lower: No data available.

Flash point°C: No data available. Part.coeff. n-octanol/water: No data available.

Autoflammability°C: No data available.

Relative density: 1.18 - 1.23 pH: No data available.

VOC g/I: No data available.

### 9.2. Other information

Other information: No data available.

### Section 10: Stability and reactivity

# 10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

# 10.2. Chemical stability

Chemical stability: Stable under normal conditions.

# 10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

### 10.4. Conditions to avoid

Conditions to avoid: < 20°C. Heat. Moist air. Humidity.

### 10.5. Incompatible materials

Materials to avoid: Water. Acids. Alcohols. Amines.

# 10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

# **Section 11: Toxicological information**

# 11.1. Information on toxicological effects

POLYCRAFT K2 PART B

Page: 7

# **Hazardous ingredients:**

# **DIPHENYLMETHANE-4,4'-DI-ISOCYANATE**

ORL	MUS	LD50	2200	mg/kg
ORL	RAT	LD50	9200	mg/kg

### Relevant hazards for substance:

Hazard	Route	Basis
Acute toxicity (ac. tox. 4)	INH	Hazardous: calculated
Skin corrosion/irritation	DRM	Hazardous: calculated
Serious eye damage/irritation	OPT	Hazardous: calculated
Respiratory/skin sensitisation	INH DRM	Hazardous: calculated
Carcinogenicity	-	Hazardous: calculated
STOT-single exposure	INH	Hazardous: calculated
STOT-repeated exposure	-	Hazardous: calculated

# Symptoms / routes of exposure

**Skin contact:** There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: Nausea and stomach pain may occur.

Inhalation: There may be a feeling of tightness in the chest with shortness of breath. Exposure may

cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

# **Section 12: Ecological information**

# 12.1. Toxicity

# **Hazardous ingredients:**

### **DIPHENYLMETHANE-4,4'-DI-ISOCYANATE**

BACTERIA (Activated Sludge)	3H EC50	> 100	mg/l

# 12.2. Persistence and degradability

Persistence and degradability: No data available.

# 12.3. Bioaccumulative potential

Bioaccumulative potential: No data available.

# 12.4. Mobility in soil

Mobility: No data available.

### 12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

### POLYCRAFT K2 PART B

Page: 8

### 12.6. Other adverse effects

Other adverse effects: No data available.

# Section 13: Disposal considerations

#### 13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal

company.

Waste code number: 08 05 01

Disposal of packaging: Arrange for collection by specialised disposal company.

NB: The user's attention is drawn to the possible existence of regional or national

regulations regarding disposal.

# **Section 14: Transport information**

Transport class: This product does not require a classification for transport.

### Section 15: Regulatory information

# 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

### 15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture

by the supplier.

# **Section 16: Other information**

# Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No

453/2010.

\* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H319: Causes serious eye irritation.

H332: Harmful if inhaled.

H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335: May cause respiratory irritation.

H351: Suspected of causing cancer <state route of exposure if it is conclusively proven

that no other routes of exposure cause the hazard>.

H373: May cause damage to organs <or state all organs affected, if known> through

prolonged or repeated exposure <state route of exposure if it is conclusively proven that

no other routes of exposure cause the hazard>.

**Legal disclaimer:** The above information is believed to be correct but does not purport to be all inclusive

and shall be used only as a guide. This company shall not be held liable for any

damage resulting from handling or from contact with the above product.

[final page]