



## SAFETY DATA SHEET

EPOXY COLOUR PASTE - CONTAINS LEAD (C.I. PIGMENT YELLOW 34)

Page: 1

Compilation date: 01/07/2015

Revision No: 2

### Section 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

**Product name:** EPOXY COLOUR PASTE - CONTAINS LEAD (C.I. PIGMENT YELLOW 34)

**Product code:** EPX

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### 1.3. Details of the supplier of the safety data sheet

**Company name:** Llewellyn Ryland Ltd

Haden Street

Birmingham

B12 9DB

United Kingdom

**Tel:** +44 (0)121 440 2284

**Fax:** +44 (0)121 440 0281

**Email:** [technical@llewellyn-ryland.co.uk](mailto:technical@llewellyn-ryland.co.uk)

#### 1.4. Emergency telephone number

**Emergency tel:** +44 (0)121 440 2284

(office hours only)

### Section 2: Hazards identification

#### 2.1. Classification of the substance or mixture

**Classification under CLP:** Repr. 1A: H360Df; Aquatic Acute 1: H400; Aquatic Chronic 1: H410; Carc. 1B: H350; Eye Irrit. 2: H319; Skin Irrit. 2: H315; Skin Sens. 1: H317; STOT RE 2: H373

**Most important adverse effects:** Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. May cause cancer. May damage the unborn child. Suspected of damaging fertility. May cause damage to organs through prolonged or repeated exposure. Very toxic to aquatic life. Very toxic to aquatic life with long lasting effects.

#### 2.2. Label elements

**Label elements:**

**Hazard statements:** H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H319: Causes serious eye irritation.

H350: May cause cancer.

H360Df: May damage the unborn child. Suspected of damaging fertility.

H373: May cause damage to organs through prolonged or repeated exposure.

H400: Very toxic to aquatic life.

H410: Very toxic to aquatic life with long lasting effects.

[cont...]

# SAFETY DATA SHEET

EPOXY COLOUR PASTE - CONTAINS LEAD (C.I. PIGMENT YELLOW 34)

Page: 2

**Signal words:** Danger

**Hazard pictograms:** GHS07: Exclamation mark

GHS08: Health hazard

GHS09: Environmental



**Precautionary statements:** P260: Do not breathe dust/fumes/gas/mist/vapours/spray.  
P280: Wear protective gloves/protective clothing/eye protection/face protection.  
P302+352: IF ON SKIN: Wash with plenty of water/.  
P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P314: Get medical attention if you feel unwell.

## 2.3. Other hazards

**PBT:** This product is not identified as a PBT/vPvB substance.

## Section 3: Composition/information on ingredients

### 3.2. Mixtures

#### Hazardous ingredients:

C.I. PIGMENT YELLOW 34

EINECS	CAS	PBT / WEL	CLP Classification	Percent
215-693-7	1344-37-2	-	Carc. 1B: H350; Repr. 1A: H360Df; STOT RE 2: H373; Aquatic Chronic 1: H410; Aquatic Acute 1: H400	30-50%

BISPHENOL A-(EPICHLORHYDRIN) {REACTION PRODUCT} - REACH registered number(s): 01-2119456619-26

500-033-5	25068-38-6	-	Eye Irrit. 2: H319; Skin Irrit. 2: H315; Skin Sens. 1: H317; Aquatic Chronic 2: H411	30-50%
-----------	------------	---	--	--------

FORMALDEHYDE, POLYMER WITH (CHLOROMETHYL) OXIRANE AND PHENOL, MW <=700 - REACH registered number(s): 01-2119454392-40

500-006-8	9003-36-5	-	Skin Irrit. 2: H315; Skin Sens. 1: H317; Aquatic Chronic 2: H411	10-30%
-----------	-----------	---	---	--------

OXIRANE, MONO[(C12-14ALKYLOXY)METHYL] DERIVATIVES - REACH registered number(s): 01-2119485289

271-846-8	68609-97-2	-	Skin Irrit. 2: H315; Skin Sens. 1: H317	1-10%
-----------	------------	---	---	-------

## Section 4: First aid measures

### 4.1. Description of first aid measures

**Skin contact:** Wash immediately with plenty of soap and water. Consult a doctor.

**Eye contact:** Bathe the eye with running water for 15 minutes. Consult a doctor.

[cont...]

# SAFETY DATA SHEET

EPOXY COLOUR PASTE - CONTAINS LEAD (C.I. PIGMENT YELLOW 34)

Page: 3

**Ingestion:** Wash out mouth with water. Consult a doctor.

**Inhalation:** Remove casualty from exposure ensuring one's own safety whilst doing so.

## 4.2. Most important symptoms and effects, both acute and delayed

**Skin contact:** There may be irritation and redness at the site of contact.

**Eye contact:** There may be irritation and redness. The eyes may water profusely.

**Ingestion:** There may be soreness and redness of the mouth and throat.

**Inhalation:** No data available.

**Delayed / immediate effects:** No data available.

## 4.3. Indication of any immediate medical attention and special treatment needed

## Section 5: Fire-fighting measures

### 5.1. Extinguishing media

**Extinguishing media:** Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.

### 5.2. Special hazards arising from the substance or mixture

**Exposure hazards:** In combustion emits toxic fumes.

### 5.3. Advice for fire-fighters

**Advice for fire-fighters:** Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

## Section 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

**Personal precautions:** Refer to section 8 of SDS for personal protection details. Turn leaking containers leak-side up to prevent the escape of liquid.

### 6.2. Environmental precautions

**Environmental precautions:** Do not discharge into drains or rivers. Contain the spillage using bunding.

### 6.3. Methods and material for containment and cleaning up

**Clean-up procedures:** Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

### 6.4. Reference to other sections

**Reference to other sections:** Refer to section 8 of SDS.

## Section 7: Handling and storage

### 7.1. Precautions for safe handling

**Handling requirements:** Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area.

[cont...]

# SAFETY DATA SHEET

EPOXY COLOUR PASTE - CONTAINS LEAD (C.I. PIGMENT YELLOW 34)

Page: 4

## 7.2. Conditions for safe storage, including any incompatibilities

**Storage conditions:** Store in a cool, well ventilated area. Keep container tightly closed.

## 7.3. Specific end use(s)

**Specific end use(s):** No data available.

## Section 8: Exposure controls/personal protection

### 8.1. Control parameters

**Workplace exposure limits:** No data available.

### DNEL/PNEC Values

**DNEL / PNEC** No data available.

### 8.2. Exposure controls

**Engineering measures:** Ensure there is sufficient ventilation of the area.

**Hand protection:** Protective gloves.

**Eye protection:** Safety glasses. Ensure eye bath is to hand.

**Skin protection:** Protective clothing.

## Section 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

**State:** Liquid

**Colour:** Various

**Odour:** Barely perceptible odour

**Viscosity:** Viscous

**Flash point°C:** >93

### 9.2. Other information

**Other information:** No data available.

## Section 10: Stability and reactivity

### 10.1. Reactivity

**Reactivity:** Stable under recommended transport or storage conditions.

### 10.2. Chemical stability

**Chemical stability:** Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

**Hazardous reactions:** Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

### 10.4. Conditions to avoid

**Conditions to avoid:** Heat. Hot surfaces. Flames.

[cont...]

# SAFETY DATA SHEET

EPOXY COLOUR PASTE - CONTAINS LEAD (C.I. PIGMENT YELLOW 34)

Page: 5

## 10.5. Incompatible materials

**Materials to avoid:** Strong oxidising agents. Strong acids.

## 10.6. Hazardous decomposition products

**Haz. decomp. products:** In combustion emits toxic fumes.

## Section 11: Toxicological information

### 11.1. Information on toxicological effects

**Hazardous ingredients:**

#### BISPHENOL A-(EPICHLORHYDRIN) {REACTION PRODUCT}

ORL	MUS	LD50	15600	mg/kg
ORL	RAT	LD50	11400	mg/kg
SKN	RBT	LD50	>20	ml/kg

#### OXIRANE, MONO[(C12-14ALKYLOXY)METHYL] DERIVATIVES

ORL	RAT	LD50	17100	mg/kg
-----	-----	------	-------	-------

**Relevant hazards for substance:**

Hazard	Route	Basis
Skin corrosion/irritation	DRM	Hazardous: calculated
Serious eye damage/irritation	OPT	Hazardous: calculated
Respiratory/skin sensitisation	DRM	Hazardous: calculated
Carcinogenicity	--	Hazardous: calculated
Reproductive toxicity	--	Hazardous: calculated
STOT-repeated exposure	-	Hazardous: calculated

## Symptoms / routes of exposure

**Skin contact:** There may be irritation and redness at the site of contact.

**Eye contact:** There may be irritation and redness. The eyes may water profusely.

**Ingestion:** There may be soreness and redness of the mouth and throat.

**Inhalation:** No data available.

**Delayed / immediate effects:** No data available.

## Section 12: Ecological information

### 12.1. Toxicity

**Ecotoxicity values:** No data available.

### 12.2. Persistence and degradability

**Persistence and degradability:** No data available.

[cont...]

# SAFETY DATA SHEET

EPOXY COLOUR PASTE - CONTAINS LEAD (C.I. PIGMENT YELLOW 34)

Page: 6

## 12.3. Bioaccumulative potential

**Bioaccumulative potential:** No data available.

## 12.4. Mobility in soil

**Mobility:** No data available.

## 12.5. Results of PBT and vPvB assessment

**PBT identification:** This product is not identified as a PBT/vPvB substance.

## 12.6. Other adverse effects

**Other adverse effects:** No data available.

## Section 13: Disposal considerations

### 13.1. Waste treatment methods

**Disposal operations:** Transfer to a suitable container and arrange for collection by specialised disposal company.

**NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

## Section 14: Transport information

### 14.1. UN number

**UN number:** UN3082

### 14.2. UN proper shipping name

**Shipping name:** ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.  
(C.I. PIGMENT YELLOW 34; EPOXY RESIN)

### 14.3. Transport hazard class(es)

**Transport class:** 9

### 14.4. Packing group

**Packing group:** III

### 14.5. Environmental hazards

**Environmentally hazardous:** Yes

**Marine pollutant:** Yes

### 14.6. Special precautions for user

**Special precautions:** No special precautions.

**Tunnel code:** E

**Transport category:** 3

## Section 15: Regulatory information

[cont...]

# SAFETY DATA SHEET

EPOXY COLOUR PASTE - CONTAINS LEAD (C.I. PIGMENT YELLOW 34)

Page: 7

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

## 15.2. Chemical Safety Assessment

## Section 16: Other information

### Other information

**Other information:** This safety data sheet is prepared in accordance with Commission Regulation (EU) No 453/2010.

**Phrases used in s.2 and s.3:** H315: Causes skin irritation.  
H317: May cause an allergic skin reaction.  
H319: Causes serious eye irritation.  
H350: May cause cancer <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>.  
H360Df: May damage the unborn child. Suspected of damaging fertility.  
H373: May cause damage to organs <or state all organs affected, if known> through prolonged or repeated exposure <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>.  
H400: Very toxic to aquatic life.  
H410: Very toxic to aquatic life with long lasting effects.  
H411: Toxic to aquatic life with long lasting effects.

**Legal disclaimer:** The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.