

# Safety Data Sheet

Revision Date: 22/Dec/2014

## 1. Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Product Description:

**POLYLITE® 32032-00**

SAP ID(s):

4887 ; 4888; 34084; 34085; 199516

Chemical Family

Polyester Resin

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended Use

Casting Resin

Sector of Uses [SU]

SU3 - Industrial uses

SU12 - Manufacture of plastics products, including compounding and conversion

SU22 - Professional uses

Product categories [PC]

PC32 - Polymer preparations and compounds

Process categories [PROC]

PROC1 - Use in closed process, no likelihood of exposure

PROC3 - Use in closed batch process (synthesis or formulation)

PROC4 - Use in batch and other process (synthesis) where opportunity for exposure arises

PROC5 - Mixing or blending in batch processes for formulation of preparations and articles (multi-stage and/or significant contact)

PROC7 - Industrial spraying

PROC8a - Transfer of substance or mixture (charging/discharging) from/to vessels/large containers at non dedicated facilities

PROC 8b - Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities

PROC9 - Transfer of substance or mixture into small containers (dedicated filling line, including weighing)

PROC10 - Roller application or brushing

PROC11 - Non industrial spraying

PROC14 - Production of mixtures or articles by tableting, compression, extrusion, pelletization

PROC15 - Use as a laboratory reagent

Uses advised against

No information available

### 1.3. Details of the supplier of the safety data sheet

**Manufacturer**

Reichhold UK Ltd.

54 Willow Road

Mitcham, Surrey

United Kingdom

CR4 4NA

+44 208 648 4684

E-mail address

prodsafety@reichhold.com

### 1.4. Emergency telephone number

(CareChem24) +44(0)1235 239670

Poison Information Center Telephone Number:

United Kingdom - Contact CareChem24

## 2. Hazards Identification

### 2.1. - Classification of the substance or mixture

**Classification according to Regulation (EC) No. 1272/2008 [CLP]**

Acute toxicity - Inhalation (Vapours)

Category 4

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2
Skin sensitisation	Category 1B
Reproductive Toxicity	Category 2
Specific target organ toxicity (single exposure)	Category 3
Specific target organ toxicity (repeated exposure)	Category 1
Chronic aquatic toxicity	Category 3
flammable liquid	Category 3

**Classification according to Directive 67/548/EEC or 1999/45/EC**

R10 - Xn;R48/20 - Xn;R20 - Xi;R36/37/38 - R43 - Repr.Cat3;R63

**2.2. Label elements****Labelling according to Regulation (EC) No. 1272/2008 [CLP]**

signal word

Danger

Contains Styrene, Methyl methacrylate

**Hazard Statements**

H315 - Causes skin irritation

H317 - May cause an allergic skin reaction

H319 - Causes serious eye irritation

H332 - Harmful if inhaled

H335 - May cause respiratory irritation

H361d - Suspected of damaging the unborn child

H372 - Causes damage to hearing through prolonged or repeated exposure if inhaled

H412 - Harmful to aquatic life with long lasting effects

H226 - Flammable liquid and vapour

62% of the mixture consists of ingredient(s) of unknown toxicity.

67.1% of the mixture consists of components(s) of unknown hazards to the aquatic environment.

**Precautionary Statements - EU (§28, 1272/2008)**

P210 - Keep away from heat, sparks, open flames, hot surfaces. - No smoking

P260 - Do not breathe mist, vapors, spray

P280 - Wear protective gloves/protective clothing/eye protection/face protection

P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing

P333 + P313 - If skin irritation or rash occurs: Get medical advice/ attention

P370 + P378 - In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish

-

**2.3. Other hazards**

No information available.

**3. Composition/information on Ingredients**

Component	EC No	CAS No	weight-%	Classification	EU - GHS Substance Classification	REACH Reg. No
-----------	-------	--------	----------	----------------	-----------------------------------	---------------

Styrene	202-851-5	100-42-5	30 - 34	Repr.Cat3; R63 Xn; R20-48/20 Xn; R65 Xi; R36/37/38 R10	Skin Irrit. 2 (H315) Flam. Liq. 3 (H226) Eye Irrit. 2 (H319) Acute Tox. 4 (H332) STOT SE 3 (H335) STOT RE 1 (H372) Repr. 2 (H361d) Asp. Tox. 1 (H304) Aquatic Chronic 3 (H412)	01-2119457861-3 2
Methyl methacrylate	201-297-1	80-62-6	< 5.5	F; R11 Xi; R37/38 Xi; R43	Skin Irrit. 2 (H315) Flam. Liq. 2 (H225) STOT SE 3 (H335) Skin Sens. 1 (H317)	01-2119452498-2 8

For the full text of the R phrases mentioned in this Section, see Section 16

For the full text of the H-Statements mentioned in this Section, see Section 16

## 4. First aid measures

### 4.1. Description of first aid measures

#### **Eye Contact**

Immediately flush eyes for at least 15 minutes. Get medical attention.

#### **Skin Contact**

Wash off with warm water and soap. Remove contaminated clothing and shoes. If skin irritation persists, call a doctor. Wash contaminated clothing before re-use.

#### **Ingestion**

Do NOT induce vomiting. This material may enter the lungs during vomiting. Never give anything by mouth to an unconscious person. Get immediate medical advice/attention.

#### **Inhalation**

Remove to fresh air. Keep patient warm and at rest. If breathing is laboured, administer oxygen. If not breathing, give artificial respiration. Get medical attention immediately.

### 4.2. Most important symptoms and effects, both acute and delayed

Irritating to eyes, respiratory system and skin. Harmful by inhalation, in contact with skin and if swallowed. MAY CAUSE ALLERGIC SKIN REACTION.

### 4.3. Indication of any immediate medical attention and special treatment needed

#### **Notes to Physician**

Treat symptomatically.

## 5. Fire-fighting measures

### 5.1. Extinguishing media

#### **Suitable Extinguishing Media**

Carbon dioxide (CO<sub>2</sub>), Foam, Dry chemical, Water spray

#### **Extinguishing media which must not be used for safety reasons**

Do not use a solid water stream as it may scatter and spread fire.

### 5.2. Special hazards arising from the substance or mixture

#### **Special exposure hazards arising from the substance or preparation itself, combustion products, resulting gases**

flammable. Vapours may form explosive mixture with air. Vapours may travel to areas away from work site before igniting/flashing back to vapour source. Combustion may produce carbon monoxide, carbon dioxide, irritating or toxic vapors and gases. Fight fire from maximum distance or use unmanned hose holders or monitor nozzles. Move containers from fire area if you can do it without risk. Cool containers with flooding quantities of water until well after fire is out. Withdraw immediately in case of rising sound from venting safety devices or discoloration of tank. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

**5.3. Advice for firefighters****Special protective equipment for fire-fighters**

Wear self-contained breathing apparatus and protective suit.

**6. Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures**

Remove all sources of ignition. Evacuate personnel to safe areas. Use personal protective equipment as required. Ensure adequate ventilation. Keep people away from and upwind of spill/leak. Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas. Avoid contact with skin and eyes. All equipment used when handling the product must be grounded.

**6.2. Environmental precautions**

Prevent further leakage or spillage if safe to do so. Do not allow material to contaminate ground water system. Prevent product from entering drains. Soak up with inert absorbent material and dispose of as hazardous waste.

**6.3. Methods and material for containment and cleaning up**

A vapour suppressing foam may be used to reduce vapours. Absorb spill with inert material (e.g. dry sand or earth), then place in a chemical waste container. Use clean non-sparking tools to collect absorbed material.

**6.4. Reference to other sections**

See Section 12 for more information

**7. Handling and Storage****7.1. Precautions for safe handling****Handling**

Do not breathe vapour or mist. Avoid contact with eyes, skin and clothing. Wash hands before breaks and immediately after handling the product. Take off contaminated clothing and wash before re-use. Ensure adequate ventilation. Ground and bond containers when transferring material. Use spark-proof tools and explosion-proof equipment. Consult your supplier of promoters and catalysts for additional instructions on proper mixing and usage. Empty containers may retain product residue (liquid and/or vapor). Do not pressurize, cut, weld, braze, solder, drill, grind, or expose these containers to heat, flame, sparks, static electricity, or other sources of ignition as the container may explode and may cause injury or death. Empty drums should be completely drained and properly bunged. Empty drums should be promptly returned to a drum reconditioner or properly disposed. Do not use compressed air for filling, discharging or handling.

**General Hygiene Considerations**

Handle in accordance with good industrial hygiene and safety practice.

**7.2. Conditions for safe storage, including any incompatibilities**

Keep away from heat and sources of ignition. No smoking. Protect from direct sunlight. Store away from incompatible materials. Keep containers tightly closed in a cool, well-ventilated place. To ensure maximum stability and maintain optimum resin properties, resins should be stored in closed containers at temperatures below 25°C.

**7.3. Specific end use(s)**

<b>Exposure scenario</b>	No information available
<b>Other Guidelines</b>	No information available

**8. Exposure Controls/Personal Protection****8.1. Control parameters****Exposure Limits**

Components with workplace control parameters.

**Styrene**

<b>Austria</b>	80 ppm STEL
	340 mg/m <sup>3</sup> STEL
	20 ppm TWA
	85 mg/m <sup>3</sup> TWA

---

<b>Belgium</b>	40 ppm TWA 173 mg/m <sup>3</sup> TWA (skin) 80 ppm STEL 346 mg/m <sup>3</sup> STEL
<b>Bulgaria</b>	85.0 mg/m <sup>3</sup> TWA 215.0 mg/m <sup>3</sup> STEL
<b>Croatia</b>	250 ppm STEL KGVI 1080 mg/m <sup>3</sup> STEL KGVI 100 ppm TWA GVI 430 mg/m <sup>3</sup> TWA GVI
<b>Czech Republic</b>	400 mg/m <sup>3</sup> Ceiling 100 mg/m <sup>3</sup> TWA (skin)
<b>Denmark</b>	25 ppm Ceiling 105 mg/m <sup>3</sup> Ceiling (skin)
<b>Estonia</b>	20 ppm TWA 90 mg/m <sup>3</sup> TWA 50 ppm STEL 200 mg/m <sup>3</sup> STEL (skin)
<b>Finland</b>	20 ppm TWA 86 mg/m <sup>3</sup> TWA 100 ppm STEL 430 mg/m <sup>3</sup> STEL
<b>France</b>	50 ppm TWA 215 mg/m <sup>3</sup> TWA 1000 mg/m <sup>3</sup> TWA 1500 mg/m <sup>3</sup>
<b>Germany</b>	20 ppm TWA 86 mg/m <sup>3</sup> TWA
<b>Greece</b>	100 ppm TWA 425 mg/m <sup>3</sup> TWA 250 ppm STEL 1050 mg/m <sup>3</sup> STEL
<b>Hungary</b>	50 mg/m <sup>3</sup> TWA AK 50 mg/m <sup>3</sup> STEL CK
<b>Ireland</b>	20 ppm TWA 85 mg/m <sup>3</sup> TWA 40 ppm STEL 170 mg/m <sup>3</sup> STEL
<b>Latvia</b>	10 mg/m <sup>3</sup> TWA 30 mg/m <sup>3</sup> STEL
<b>Lithuania</b>	20 ppm TWA (IPRD) 90 mg/m <sup>3</sup> TWA (IPRD) 10 ppm TWA (IPRD) 50 ppm STEL (TPRD) 200 mg/m <sup>3</sup> STEL (TPRD) (skin)
<b>Norway</b>	25 ppm TWA 105 mg/m <sup>3</sup> TWA M 37.5 ppm STEL 131.25 mg/m <sup>3</sup> STEL
<b>Poland</b>	200 mg/m <sup>3</sup> STEL 50 mg/m <sup>3</sup> TWA
<b>Portugal OELs Data</b>	20 ppm 40 ppm STEL
<b>Romania</b>	12 ppm TWA 50 mg/m <sup>3</sup> TWA 35 ppm STEL 150 mg/m <sup>3</sup> STEL

---

<b>Russia</b>	10 mg/m <sup>3</sup> TWA (vapor) 30 mg/m <sup>3</sup> STEL (vapor)
<b>Slovakia</b>	20 ppm TWA 86 mg/m <sup>3</sup> TWA
<b>Slovenia</b>	200 mg/m <sup>3</sup> Ceiling 20 ppm TWA 86 mg/m <sup>3</sup> TWA 80 ppm STEL 344 mg/m <sup>3</sup> STEL
<b>Spain</b>	20 ppm TWA 86 mg/m <sup>3</sup> TWA 40 ppm STEL 172 mg/m <sup>3</sup> STEL
<b>Sweden</b>	10 ppm LLV 43 mg/m <sup>3</sup> LLV 20 ppm STV 86 mg/m <sup>3</sup> STV (skin)
<b>Switzerland</b>	40 ppm STEL 170 mg/m <sup>3</sup> STEL 20 ppm TWA 85 mg/m <sup>3</sup> TWA
<b>United Kingdom</b>	100 ppm TWA 430 mg/m <sup>3</sup> TWA 250 ppm STEL 1080 mg/m <sup>3</sup> STEL
<b>ACGIH - TLV</b>	20 ppm TWA 40 ppm STEL
<b>Methyl methacrylate</b>	
<b>European Union</b>	100 ppm Indicative 50 ppm Indicative
<b>Austria</b>	100 ppm STEL 420 mg/m <sup>3</sup> STEL 50 ppm TWA 210 mg/m <sup>3</sup> TWA
<b>Belgium</b>	50 ppm TWA 208 mg/m <sup>3</sup> TWA 100 ppm STEL 416 mg/m <sup>3</sup> STEL
<b>Bulgaria</b>	50 ppm TWA 100 ppm STEL
<b>Croatia</b>	100 ppm STEL KGV 50 ppm TWA GVI
<b>Cyprus</b>	100 ppm STEL 50 ppm TWA
<b>Czech Republic</b>	150 mg/m <sup>3</sup> Ceiling 50 mg/m <sup>3</sup> TWA (skin)
<b>Denmark</b>	25 ppm 102 mg/m <sup>3</sup> (skin)
<b>Estonia</b>	50 ppm TWA 200 mg/m <sup>3</sup> TWA 150 ppm STEL 600 mg/m <sup>3</sup> STEL (skin)
<b>Finland</b>	10 ppm TWA 42 mg/m <sup>3</sup> TWA 50 ppm STEL 210 mg/m <sup>3</sup> STEL

---

<b>France</b>	50 ppm TWA 205 mg/m <sup>3</sup> TWA 100 ppm 410 mg/m <sup>3</sup>
<b>Germany</b>	50 ppm TWA 210 mg/m <sup>3</sup> TWA
<b>Greece</b>	50 ppm TWA 100 ppm STEL
<b>Hungary</b>	208 mg/m <sup>3</sup> TWA AK 415 mg/m <sup>3</sup> STEL CK (skin)
<b>Ireland</b>	50 ppm TWA 100 ppm STEL
<b>Italy</b>	50 ppm TWA 100 ppm STEL
<b>Latvia</b>	10 mg/m <sup>3</sup> TWA
<b>Lithuania</b>	50 ppm TWA (IPRD) 200 mg/m <sup>3</sup> TWA (IPRD) 100 ppm STEL (TPRD) 400 mg/m <sup>3</sup> STEL (TPRD)
<b>Luxembourg</b>	50 ppm TWA 100 ppm STEL
<b>The Netherlands</b>	410 mg/m <sup>3</sup> STEL 205 mg/m <sup>3</sup> TWA
<b>Norway</b>	25 ppm TWA 100 mg/m <sup>3</sup> TWA A 100 ppm STEL 400 mg/m <sup>3</sup> STEL (skin)
<b>Poland</b>	300 mg/m <sup>3</sup> STEL 100 mg/m <sup>3</sup> TWA
<b>Portugal OELs Data</b>	50 ppm 100 ppm STEL
<b>Romania</b>	50 ppm TWA 205 mg/m <sup>3</sup> TWA 100 ppm STEL 410 mg/m <sup>3</sup> STEL
<b>Russia</b>	10 mg/m <sup>3</sup> TWA (vapor) 20 mg/m <sup>3</sup> STEL (vapor)
<b>Slovakia</b>	50 ppm TWA 210 mg/m <sup>3</sup> TWA 420 mg/m <sup>3</sup> Ceiling
<b>Slovenia</b>	50 ppm TWA 210 mg/m <sup>3</sup> TWA 100 ppm STEL 420 mg/m <sup>3</sup> STEL
<b>Spain</b>	50 ppm TWA 100 ppm STEL
<b>Sweden</b>	50 ppm LLV 200 mg/m <sup>3</sup> LLV 150 ppm STV 600 mg/m <sup>3</sup> STV (skin)
<b>Switzerland</b>	100 ppm STEL 420 mg/m <sup>3</sup> STEL 50 ppm TWA 210 mg/m <sup>3</sup> TWA
<b>United Kingdom</b>	50 ppm TWA 208 mg/m <sup>3</sup> TWA 100 ppm STEL 416 mg/m <sup>3</sup> STEL





<b>Styrene</b>	End Use: Workers Exposure Route: Inhalation Exposure Type: Acute, systemic effects Value: 289 mg/m <sup>3</sup> (68 ppm)	Fresh water Value: 0.028 mg/l Assessment factor: 10
	End Use: Workers Exposure Route: Inhalation Exposure Type: Acute, local effects Value: 306 mg/m <sup>3</sup> (72 ppm)	Sea water Value: 0.0028 mg/l Assessment factor: 100
	End Use: Workers Exposure Route: Inhalation Exposure Type: Long term, systemic effects Value: 85 mg/m <sup>3</sup> (20 ppm)	Water Value: 0.04 mg/l Intermittent Releases Assessment factor: 100
	End Use: Workers Exposure Route: Dermal Exposure Type: Long term, systemic effects Value: 406 mg/kg bw/day	Fresh water sediment Value: 0.614 mg/kg dw
	End Use: General Population Exposure Route: Inhalation Exposure Type: Acute, systemic effects Value: 174.25 mg/m <sup>3</sup> (41 ppm)	Sea sediment Value: 0.0614 mg/kg dw
	End Use: General Population Exposure Route: Inhalation Exposure Type: Acute, local effects Value: 182.75 mg/m <sup>3</sup> (43 ppm)	Sewage Treatment Plant Value: 5 mg/l Assessment factor: 100
	End Use: General Population Exposure Route: Inhalation Exposure Type: Long term, systemic effects Value: 10.2 mg/m <sup>3</sup> (2.4 ppm)	Soil Value: 0.2 mg/kg dw
	End Use: General Population Exposure Route: Dermal Exposure Type: Long term, systemic effects Value: 343 mg/kg bw/day	

<b>Methyl methacrylate</b>	End Use: Workers Exposure Route: Dermal Exposure Type: Acute, local effects Value: 1.5 mg/cm <sup>2</sup>	Fresh water Value: 0.94 mg/l
	End Use: Workers Exposure Route: Dermal Exposure Type: Long term, systemic effects Value: 13.67 mg/kg bw/day	Marine water Value: 0.094 mg/l
	End Use: Workers Exposure Route: Inhalation Exposure Type: Long term, systemic effects Value: 210 mg/m <sup>3</sup> (51.3 ppm)	Intermittent releases Value: 0.94 mg/l
	End Use: Workers Exposure Route: Dermal Exposure Type: Long term, local effects Value: 1.5 mg/cm <sup>2</sup>	Sewage Treatment Plant Value: 10 mg/l
	End Use: Workers Exposure Route: Inhalation Exposure Type: Long term, local effects Value: 210 mg/m <sup>3</sup> (51.3 ppm)	Fresh water sediment Value: 5.74 mg/kg dw
	End Use: General Population Exposure Route: Dermal Exposure Type: Acute, local effects Value: 1.5 mg/cm <sup>2</sup>	Soil Value: 1.47 mg/kg dw
	End Use: General Population Exposure Route: Dermal Exposure Type: Long term, systemic effects Value: 8.2 mg/kg bw/day	
	End Use: General Population Exposure Route: Inhalation Exposure Type: Long term, systemic effects Value: 74.3 mg/m <sup>3</sup> (18.2 ppm)	
	End Use: General Population Exposure Route: Dermal Exposure Type: Long term, local effects Value: 1.5 mg/cm <sup>2</sup>	
	End Use: General Population Exposure Route: Inhalation Exposure Type: Long term, local effects Value: 105 mg/m <sup>3</sup> (25.7 ppm)	

**8.2. Exposure controls**  
**Engineering controls**

Use general ventilation to maintain airborne concentrations to levels that are below regulatory and recommended occupational exposure limits. Local ventilation may be required during certain operations. Use explosion-proof equipment.

**Personal Protective Equipment**

<b>Eye Protection</b>	Safety glasses with side-shields conforming to EN166. If splashes are likely to occur: Tightly fitting safety goggles (EN166). Ensure that eyewash stations and safety showers are close to the workstation location.
<b>Skin protection</b>	Impervious clothing.
<b>Hand Protection</b>	Protective gloves complying with EN 374. Wear protective nitrile rubber or Viton™ gloves. Gloves made of nitrile rubber or polyvinyl chloride (PVC) may be used for splash protection and brief or intermittent contact with styrenated polyester resin. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion.
<b>Respiratory protection</b>	None required if hazards have been assessed and airborne concentrations are maintained below the exposure limits listed in Section 8. Wear an approved air-purifying respirator with organic vapor cartridges and particulate filters where airborne concentrations may exceed exposure limits in Section 8 and/or there is exposure to dust or mists due to sanding, grinding, cutting, or spraying. Use an approved positive-pressure air-supplied respirator with emergency escape provisions if there is any potential for an uncontrolled release, airborne concentrations are not known, or any other circumstances where air-purifying respirators may not provide adequate protection.
<b>Recommended Filter type:</b>	Type A (EN141) and Type P2 (EN143)
<b>Environmental exposure controls</b>	Local authorities should be advised if significant spillages cannot be contained.

## 9. Physical and Chemical Properties

### 9.1. Information on basic physical and chemical properties

<b>Appearance</b>	blue	<b>Physical State</b>	Liquid
<b>Odour</b>	Pungent	<b>Odour Threshold</b>	0.2 ppm (Styrene) 0.05 - 0.21 ppm (Methyl Methacrylate)
<b>pH</b>	Not applicable	<b>Remarks</b>	<u>Method</u>
<b>Melting point / Freezing point</b>	Not applicable		None known
<b>Boiling point / boiling range</b>	100°C - 146°C		None known
<b>Flash Point</b>	26 °C		Seta closed cup (ISO 3679)
<b>Evaporation Rate</b>	0.49 - 3.1 (BuAc = 1)		None known
<b>Flammability Limit in Air</b>			None known
<b>Upper</b>	12.5%		
<b>Lower</b>	1.1%		
<b>Vapour Pressure</b>	6.7 - 27 hPa @ 20°C		None known
<b>Vapour Density</b>	3.6 - 3.94 (Air = 1)		None known
<b>specific gravity</b>	1.1 - 1.3 @ 23°C		None known
<b>Solubility</b>	Insoluble (Water)		None known
<b>Partition coefficient: n-octanol/water</b>	No information available		None known
<b>Autoignition Temperature</b>	430°C - 490°C		(DIN 51794)
<b>Decomposition temperature</b>	No information available		None known
<b>Viscosity</b>	300 - 400 mPas @ 23°C		Cone & Plate
<b>Explosive properties</b>	No information available		
<b>Oxidising properties</b>	No information available		

### 9.2. OTHER INFORMATION

No information available

## 10. Stability and Reactivity

### 10.1. Reactivity

Unstable upon depletion of inhibitor.

### 10.2. Chemical stability

Stable under normal conditions. Stable under recommended storage conditions.

### **10.3. Possibility of hazardous reactions**

Polymerisation can occur. Hazardous polymerization will occur if contaminated with peroxides, metal salts and polymerization catalysts. Product will undergo hazardous polymerization at temperatures above 150 F (65 C). Hazardous polymerization may occur upon depletion of inhibitor - may cause heat and pressure build-up in closed containers.

### **10.4. Conditions to Avoid**

Heat, flames and sparks. Contamination by those materials referred to under Incompatible materials. Unstable upon depletion of inhibitor. Elevated temperatures.

### **10.5. incompatible materials**

Strong acids. Strong oxidising agents. Metal salts. Polymerization initiators. Copper. Copper alloys. Brass.

### **10.6. Hazardous Decomposition Products**

Hydrocarbons. Carbon monoxide. Carbon dioxide (CO<sub>2</sub>). Thermal decomposition can lead to release of irritating and toxic gases and vapours.

## **11. Toxicological Information**

### **11.1. Information on toxicological effects**

#### **Acute toxicity**

##### **Inhalation**

Harmful by inhalation. May cause irritation of respiratory tract. Inhalation of high vapor concentrations can cause CNS depression and narcosis.

##### **Eye Contact**

Irritating to eyes.

##### **Skin Contact**

Causes skin irritation. May cause sensitisation by skin contact. Prolonged skin contact may defat the skin and produce dermatitis.

##### **Ingestion**

HARMFUL IF SWALLOWED. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhoea. ASPIRATION HAZARD IF SWALLOWED - CAN ENTER LUNGS AND CAUSE DAMAGE.

#### **Styrene**

Oral LD50

= 5000 mg/kg (Rat)

dermal LD50

> 2000 mg/kg (Rat)

Inhalation LC50

= 11.8 mg/l (4 H) (Rat)

#### **Methyl methacrylate**

Oral LD50

= 7872 mg/kg (Rat)

#### **Irritation**

Irritating to eyes and skin.

#### **corrosivity**

Not corrosive.

#### **Sensitisation**

Contains methacrylates, which are known to be weak sensitizers.

#### **Carcinogenic effects**

There is no convincing evidence that styrene possesses significant carcinogenic potential in humans.

#### **Repeated dose toxicity**

In humans, styrene may cause a transient decrease in color discrimination and effects on hearing. Repeated or prolonged exposure may cause skin irritation and dermatitis, due to defatting properties of the product. May cause damage to the kidneys, liver, eyes, brain, respiratory system, central nervous system through prolonged or repeated exposure if inhaled. May cause damage to the liver, eyes, brain, respiratory system, central nervous system through prolonged or repeated exposure if inhaled.

#### **Mutagenic effects**

Styrene has given mixed positive and negative results in a number of mutagenicity tests. Styrene was not mutagenic without metabolic activation but gave negative and positive mutagenic results with metabolic activation.

#### **Target organ(s)**

Liver, Kidney, Central Nervous System (CNS), Respiratory system, Skin.

**Numerical measures of toxicity - Product Information**

**Unknown acute toxicity** 62% of the mixture consists of ingredient(s) of unknown toxicity.

The following values are calculated based on chapter 3.1 of the GHS document

<b>ATEmix (oral)</b>	5899 mg/kg
<b>ATEmix (dermal)</b>	2361 mg/kg
<b>ATEmix (inhalation-vapour)</b>	13.1 mg/l

**12. Ecological Information****12.1. Toxicity**

**Ecotoxicity effects:** .

**Styrene**

Algae	EC50 = 1.4 mg/L (Pseudokirchneriella subcapitata) (72h) EC50 0.46 - 4.3 mg/L (Pseudokirchneriella subcapitata) (72h)
Fish	LC50 3.24 - 4.99 mg/L (Pimephales promelas) (96 h) flow-through LC50 19.03 - 33.53 mg/L (Lepomis macrochirus) (96 h) static LC50 6.75 - 14.5 mg/L (Pimephales promelas) (96 h) static LC50 58.75 - 95.32 mg/L (Poecilia reticulata) (96 h) static
Aquatic Invertebrates	EC50 3.3 - 7.4 mg/L (Daphnia magna) (48h)

**Methyl methacrylate**

Fish	LC50 243 - 275 mg/L (Pimephales promelas) (96 h) flow-through LC50 125.5 - 190.7 mg/L (Pimephales promelas) (96 h) static LC50 170 - 206 mg/L (Lepomis macrochirus) (96 h) flow-through LC50 153.9 - 341.8 mg/L (Lepomis macrochirus) (96 h) static LC50 > 79 mg/L (Oncorhynchus mykiss) (96 h) flow-through LC50 > 79 mg/L (Oncorhynchus mykiss) (96 h) static
Aquatic Invertebrates	LC50 326.4 - 426.9 mg/L (Poecilia reticulata) (96 h) static EC50 = 69 mg/L (Daphnia magna) (48h)

**12.2. Persistence and degradability**

No information available.

**12.3. Bioaccumulative potential**

Bioaccumulation is unlikely.

**Styrene**

log Kow	2.95
Bioconcentration factor (BCF)	74

**Methyl methacrylate**

log Kow	0.7
---------	-----

**12.4. Mobility in soil**

No information available.

**12.5. Results of PBT and vPvB assessment**

This preparation contains no substance considered to be persistent, bioaccumulating This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB).

**12.6. Other adverse effects**

No information available

**13. Disposal Considerations****13.1. Waste treatment methods****Waste from residues/unused products**

This material and its container must be disposed of as hazardous waste. Dispose of contents/containers in accordance with local regulations. Can be incinerated, when in compliance with local regulations.

**Contaminated packaging**

Empty containers should be taken for local recycling, recovery or waste disposal.

**EWC Waste Disposal No** 07 00 00 WASTES FROM ORGANIC CHEMICAL PROCESSES  
 07 02 00 Wastes from MFSU of plastics, synthetic rubber and man-made fibres  
 07 02 99 Wastes not otherwise specified

## 14. Transport information

### ADR/RID

**UN-No** UN1866  
**Proper shipping name** RESIN SOLUTION  
**Hazard Class** 3  
**Packing group** III  
**Environmental hazard** None  
**Classification code** F1  
**Hazard identification number (Kemler No.)** 30  
**Tunnel restriction code** D/E  
**ADR Exception** This material meets the viscosity criteria specified in ADR 2.2.3.1.5 and may be classed as "not dangerous" when packaged in containers of less than 450 liters.

### IMDG/IMO

**UN-No** UN1866  
**Proper shipping name** RESIN SOLUTION  
**Hazard Class** CLASS 3  
**Packing group** PG III  
**Environmental hazard** None  
**EmS-No** F-E, S-E  
**IMDG Exception** This material meets the viscosity criteria specified in IMDG Code 2.3.2.5 and may be exempt from the marking, labelling and package testing requirements if transported in containers of 30 liters or less.

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code** No information available

### IATA

**UN-No** UN1866  
**Proper shipping name** RESIN SOLUTION  
**Hazard Class** 3  
**Packing group** III  
**Environmental hazard** None  
**Packing Instructions** 355; 366

## 15. Regulatory Information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### Denmark

##### **List of substances and processes that are considered to be carcinogenic**

Component	Status
Styrene (CAS #: 100-42-5)	Present

##### **Additional information**

Must not be used by youngsters under the age of 18, ref. the notification from the Ministry of Labour regarding work by youngsters. The user must have undergone special training approved by the Labour Inspection Authority (AT) in order to work with products containing carcinogenic substances.

#### Germany

**WGK Classification (VwVwS)**

Hazardous to water/Class 2

**Netherlands**

No information available

**Water Hazard Class**

10-May cause long-term adverse effects in the aquatic environment.

**International Inventories**

<b>TSCA Inventory Status:</b>	All components of this material are listed on the US Toxic Substances Control Act (TSCA) inventory.
<b>Canadian Inventory Status:</b>	All components of this material are listed on the Canadian Domestic Substances List (DSL).
<b>Australian Inventory Status:</b>	This product contains only chemicals which are currently listed on the Australian Inventory of Chemical Substances. This product contains one or more chemicals currently not on the Australian Inventory of Chemical Substances.
<b>Korean Inventory Status:</b>	This product contains only chemicals which are currently listed on the Korean Chemical Substances List. This product contains one or more chemicals currently not on the Korean Chemical Substances List.
<b>Philippine Inventory:</b>	This product contains one or more chemicals currently not on the Philippine Inventory of Chemicals and Chemical Substances.
<b>Japan ENCS:</b>	This product contains only chemicals that are currently listed on the Japanese Inventory of Existing and New Chemical Substances. This product contains one or more chemicals currently not on the Japanese Inventory of Existing and New Chemical Substances.
<b>Chinese IECS:</b>	This product contains only chemicals that are currently listed on the Chinese Inventory of Existing Chemical Substances. This product contains one or more chemicals currently not on the Chinese Inventory of Existing Chemical Substances.
<b>New Zealand Inventory:</b>	This product contains only chemicals which are currently listed on the New Zealand Inventory of Chemicals. This product contains one or more chemicals currently not on the New Zealand Inventory of Chemicals.

**Product Registrations**

<b>Norway</b>	Not applicable
---------------	----------------

**16. Other Information****Classification procedure:**

Acute toxicity - Inhalation (Vapours)	Calculation method
Skin corrosion/irritation	Calculation method
Serious eye damage/eye irritation	Calculation method
Skin sensitisation	Calculation method
Reproductive Toxicity	Weight of evidence
Specific target organ toxicity (single exposure)	Calculation method
Specific target organ toxicity (repeated exposure)	Calculation method
Chronic aquatic toxicity	Calculation method
flammable liquid	On basis of test data

**Text of R phrases mentioned in Section 3**

R10 - Flammable

R11 - Highly flammable

R20 - Harmful by inhalation

R43 - May cause sensitisation by skin contact

R63 - Possible risk of harm to the unborn child

R65 - Harmful: may cause lung damage if swallowed

R36/38 - Irritating to eyes and skin

R37/38 - Irritating to respiratory system and skin

R36/37/38 - Irritating to eyes, respiratory system and skin

R48/20 - Harmful: danger of serious damage to health by prolonged exposure through inhalation

**Full text of H-Statements referred to under sections 2 and 3**

H225 - Highly flammable liquid and vapour

H226 - Flammable liquid and vapour

H302 - Harmful if swallowed

H304 - May be fatal if swallowed and enters airways

H315 - Causes skin irritation

H317 - May cause an allergic skin reaction

H319 - Causes serious eye irritation

H332 - Harmful if inhaled

H335 - May cause respiratory irritation

H361d - Suspected of damaging the unborn child

H372 - Causes damage to hearing through prolonged or repeated exposure if inhaled

H412 - Harmful to aquatic life with long lasting effects

Denmark Arbejdstilsynet Order no. 908 of 27 September 2005 with subsequent amendments

**Prepared By**

Reichhold Product Regulatory Department  
Phone Number: +1-919-990-7500

**Revision Date:**

22/Dec/2014

**Revision Summary:**

This data sheet contains changes from the previous version in section(s):  
2, 3, 4, 8, 11, 15, 16

**Former date**

25 October 2013

This information is provided in good faith and is correct to the best of Reichhold's knowledge as of the date hereof and is designed to assist our customers; however, Reichhold makes no representation as to its completeness or accuracy. Our products are intended for sale to industrial and commercial customers. We require customers to inspect and test our products before use and to satisfy themselves as to suitability for their specific applications. Any use which Reichhold customers or third parties make of this information, or any reliance on, or decisions made based upon it, are the responsibility of such customer or third party. Reichhold disclaims responsibility for damages, or liability, of any kind resulting from the use of this information. THERE ARE NO WARRANTIES OR REPRESENTATIONS, EXPRESS OR IMPLIED, INCLUDING THOSE OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE WITH RESPECT TO THIS INFORMATION OR TO THE PRODUCT IT DESCRIBES. IN NO EVENT SHALL REICHHOLD BE LIABLE FOR SPECIAL, INCIDENTAL, OR CONSEQUENTIAL DAMAGES.

**End of Safety Data Sheet**