

1. Identification

Product Identifier: **PT Flex 20 Liquid Rubber Part B**
 Product Code(s): PTFLEX20B
 Use: Component for Liquid Polyurethane Casting Rubber. For Industrial/Professional use only.
 Manufacturer: Polytek Development Corp.
 55 Hilton St., Easton, PA 18042 USA
 Phone Number: +1 610-559-8620 (9 a.m. to 5 p.m. EST)
 Emergency Phone: CHEMTREC 800-424-9300 or +1 703-527-3887
 E-mail: sds@polytek.com

2. Hazards Identification

GHS Classification:
 Specific Target Organ Toxicity - Repeated Exposure Category 2

Label Elements: Warning



Contains diethyltoluenediamine

Hazard Phrases

H373 May cause damage to organs (pancreas) through prolonged or repeated exposure.

Precautionary Phrases

P260 Do not breathe vapors.
 P314 Get medical advice if you feel unwell.
 P501 Dispose of contents and container in accordance with local, regional and national regulations.

Supplemental Information: May cause eye and skin irritation. This is one part of a two-part system. Read and understand the hazard information on Part A before using.

3. Composition/Information on Ingredients

Chemical Name	CAS #	%
Diethyltoluenediamine	68479-98-1	2%
Other ingredients are not classified as health and/or environmental hazards, and/or are present below cut-off/concentration limits.		

4. First-Aid Measures

Eye Contact: Rinse thoroughly with water, holding the eyelids open to be sure the material is washed out. Get medical attention if irritation persists.

Skin Contact: Remove contaminated clothing. Wash contact area thoroughly with soap and water. Get medical attention if irritation persists.

Inhalation: Remove person to fresh air. Get medical attention if symptoms persist.

Ingestion: Do not induce vomiting unless directed to do so by medical personnel. Get medical attention.

Most Important Symptoms/Effects: May cause mild eye and skin irritation. May be harmful if swallowed.

Indication of Immediate Medical Attention/Special Treatment: Immediate medical attention is not required.

5. Fire-Fighting Measures

Extinguishing Media: Use water fog, foam, carbon dioxide or dry chemical. Do not use solid water stream. Solid stream of water into hot product may cause violent steam generation or eruption.

Specific Hazards: Not classified as flammable or combustible. Product will burn under fire conditions.

Special Protective Equipment & Precautions for Fire-Fighters: Wear positive pressure, self-contained breathing apparatus and full-body protective clothing. Cool fire-exposed containers with water.

6. Accidental Release Measures

Personal Precautions, Protective Equipment and Emergency Procedures: Remove all ignition sources. Clear non-emergency personnel from the area. Wear appropriate protective clothing to prevent eye and skin contact and avoid breathing vapors. Caution – spill area may be slippery.

Methods and Materials for Containment and Cleanup: Cover with an inert absorbent material and collect into an appropriate container for disposal. Avoid releases to the environment. Report spills and releases as required to appropriate authorities.

7. Handling and Storage

Safe Handling: Use with adequate ventilation. Avoid contact with the eyes, skin and clothing. Wash thoroughly after handling. Do not eat, drink or smoke in the work area. Keep container closed when not in use.

Safe Storage: Store indoors at 60-95°F (15-35°C). Store in original containers. Avoid getting moisture into containers. Keep containers tightly closed.

8. Exposure Controls/Personal Protection

Occupational Exposure Limits: None Established

Ventilation: Use with adequate general or local exhaust ventilation to minimize exposure.

Respiratory Protection: If needed, an approved respirator with organic vapor cartridges may be used. Respirator selection and use should be based on contaminant type, form and concentration. For higher exposures or in an emergency, use a supplied-air respirator.

Skin Protection: Wear impervious gloves, such as butyl rubber or nitrile rubber.

Eye Protection: Wear chemical safety glasses or goggles.

Other Protective Measures: Wear impervious clothing to prevent skin contact and contamination of personal clothing. An eye wash facility and washing facility should be available in the work area. Follow applicable regulations and good Industrial Hygiene practice.

9. Physical and Chemical Properties

Appearance: Tan, opaque liquid

Odor: No data available

Odor Threshold: No data available

pH: Not applicable

Melting Point: No data available

Boiling Point: No data available

Flash Point: > 350°F (>177°C)

Evaporation Rate: No data available

Upper/Lower Flammability Limits: No data available

Vapor Pressure: <0.01 mm Hg @ 25°C

Vapor Density: No data available

Relative Density: 1.0 @ 25°C

Solubility: Slightly soluble in water

Partition Coefficient: n-octanol/Water: No data available

Auto-Ignition Temp: No data available

Decomposition Temp: No data available

Viscosity: 720 cP

10. Stability and Reactivity

Reactivity: Not normally reactive.

Chemical Stability: Stable under recommended conditions.

Possibility of Hazardous Reactions: Reaction with strong oxidizers generates heat.

Conditions to Avoid: Avoid excessive heat.

Incompatible Materials: Avoid contact with strong oxidizers.

Hazardous Decomposition Products: Thermal decomposition will generate oxides of carbon and nitrogen, organic acids, and other toxic organic compounds.

11. Toxicological Information

Eye Contact: May cause moderate irritation.

Skin Contact: May cause mild irritation.

Inhalation: Vapor and mists may cause mild respiratory irritation.

Ingestion: Not fully determined, but single oral dose toxicity is low. Ingesting large amounts may cause adverse gastrointestinal effects.

Chronic Health Effects: Not determined; but, based on laboratory animal studies, diethyltoluenediamine ingredient may cause damage to the pancreas, liver, thyroid and eyes through prolonged exposure.

Acute Toxicity Values:

For Diethyltoluenediamine: Oral rat LD50 738 mg/kg; Inhalation rat LC50 2.45 mg/L/1 hr; Dermal rabbit LD50 >2000 mg/kg

Skin Corrosion/Irritation: Components are not classified as skin irritants.

Eye Damage/Irritation: Components are not classified as eye irritants.

Respiratory Irritation: Components are not classified as respiratory irritants.

Respiratory Sensitization: Components are not classified as respiratory sensitizers.

Skin Sensitization: Components are not classified as skin sensitizers.

Germ Cell Mutagenicity: Components are not classified as mutagens.

Carcinogenicity: Components are not classified as carcinogens.

Reproductive Toxicity: Components are not classified as reproductive toxins.

Specific Target Organ Toxicity:

Single Exposure: No data available

Repeat Exposure: Diethyltoluenediamine may cause damage to the pancreas through repeated or prolonged exposure.

12. Ecological Information

Ecotoxicity: One ingredient is harmful to aquatic organisms: diethyltoluenediamine (Fish LC50 200 mg/L/48 hr; Daphnia EC50 0.5 mg/L/48 hr). But, based on Additivity Formula, product is not classed as hazardous to the aquatic environment.

Persistence and Degradability: Not readily biodegradable.

Bioaccumulative Potential: Not expected to bioaccumulate.

Mobility in Soil: No data available.

13. Disposal Considerations

Dispose according to local, state and federal regulations.

14. Transport Information

Not regulated for transport by any mode.

Emergency Shipping Information: CHEMTREC, 800-424-9300 or +1-703-527-3887

15. Regulatory Information

U.S. FEDERAL REGULATIONS:

CERCLA 103 Reportable Quantity: This product is not subject to reporting under CERCLA. Some states have more stringent reporting requirements. Report all spills in accordance with local, state, and federal regulations.

SARA TITLE III

Section 311/312: Chronic Health

Section 313 Toxic Chemicals: This product contains no chemicals subject to SARA Title III Section 313 Reporting requirements.

Section 302 Extremely Hazardous Substances (TPQ): None

EPA Toxic Substances Control Act (TSCA) Status: All component in this product are listed on TSCA.

STATE REGULATIONS:

California Proposition 65: No CA Proposition 65 warning is required.

16. Other Information

Training Advice: All personnel using/handling this product should be trained in proper chemical handling and the need for and use of engineering controls and protective equipment.

Recommended Uses and Restrictions: This product is intended for industrial/professional use only.

SDS Revision Notes: New GHS format and classification.

Disclaimer: The information contained herein is considered accurate; however, Polytek® Development Corp. makes no warranty regarding the accuracy of the information. The user must determine the suitability of the product for the intended use and accepts all risk and liability associated with that use.