Polycraft Polyfoam Rigid 145 Part B

Page: 1 Compilation date: 15/05/15 Revision date: 17/10/15 Revision No: 2

1.1. Product identifier Product name: Polycraft Polyfoam Rigid 145 Part B			
CAS number:	9016-87-9		
I.2. Relevant identified uses of the substance or mixture and uses advised against			
Use of substance / mixture:	Production of polyurethane foam.		
1.3. Details of the supplier of the safety data sheet			
Company name: MB Fibreglass			
	Unit 17 &20 Abbey Business Park		
	Mill Road		
	Newtownabbey		
	BT36 7EE		
	United Kingdom		
Tel:	02890 861992		
Email:	sales@mbfg.co.uk		

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP:

Eye Irrit. 2: H319; Acute Tox. 4: H332; Carc. 2: H351; Resp. Sens. 1: H334; Skin Irrit. 2: H315; Skin Sens. 1: H317; STOT RE 2: H373; STOT SE 3: H335

Most important adverse effects:

Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Harmful if inhaled. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause respiratory irritation. Suspected of causing cancer. May cause damage to organs through prolonged or repeated exposure.

2.2. Label elements

Label elements: Hazard statements:	H315: Causes skin irritation.
	H317: May cause an allergic skin reaction. H319: Causes serious eye irritation. H332: Harmful if inhaled.
	H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled.
	H335: May cause respiratory irritation. H351: Suspected of causing cancer.
	H373: May cause damage to organs through prolonged or repeated exposure.
Hazard pictograms:	GHS07: Exclamation mark

SAFETY DATA SHEET Polycraft Polyfoam Rigid 145 Part B

Page: 2

GHS08: Health hazard



Signal words:

Precautionary statements:

P260: Do not breathe dust/fumes/gas/mist/vapours/spray.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P302+352: IF ON SKIN: Wash with plenty of water/.

P304+340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P304+341: IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing.

P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P403+233: Store in a well-ventilated place. Keep container tightly closed.

P501: Dispose of contents to specialist waste collection point, or react with other component to give non-hazardous foam.

2.3. Other hazards

PBT:

This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.1. Substances

Chemical identity: DIPHENYLMETHANE DIISOCYANATE (ISOMERS AND HOMOLOGUES) **CAS number:** 9016-87-9

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water.
Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.
Ingestion: Wash out mouth with water. Consult a doctor.
Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact:There may be irritation and redness at the site of contact.Eye contact:There may be irritation and redness. The eyes may water profusely.Ingestion:There may be soreness and redness of the mouth and throat.Inhalation:There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause
coughing or wheezing.Delayed/immediate effects:Immediate effects: can be expected after short-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

SAFETY DATA SHEET Polycraft Polyfoam Rigid 145 Part B

Page: 3

Section 5: Fire-fighting measures

Immediate / special treatment: Eye bathing equipment should be available on the premises.

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters:

Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions:

Refer to section 8 of SDS for personal protection details. If outside do not approach from downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of liquid.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Avoid the formation or spread of mists in the air.

Polycraft Polyfoam Rigid 145 Part B

Page: 5

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed.

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

DIPHENYLMETHANE DIISOCYANATE (ISOMERS AND HOMOLOGUES)

Workplace exposure limits:

Respirable dust

	State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
I	UK	0.02 mg/m3	0.07 mg/m3	-	-

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area.
Respiratory protection: Self-contained breathing apparatus must be available in case of emergency.
Hand protection: Protective gloves.
Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Protective clothing.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Liquid Viscosity: Viscous Boiling point/range°C: 330

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Polycraft Polyfoam Rigid 145 Part B

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions. Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

DIPHENYLMETHANE DIISOCYANATE (ISOMERS AND HOMOLOGUES)

ORL	RAT	LD50	49	gm/kg
SKN	RBT	LD50	>9400	mg/kg

Relevant hazards for product:

Hazard	Route	Basis	
Acute toxicity (ac. tox. 4)	INH	Hazardous: calculated	
Skin corrosion/irritation	DRM	Hazardous: calculated	
Serious eye damage/irritation	ΟΡΤ	Hazardous: calculated	
Respiratory/skin sensitisation	INH DRM	Hazardous: calculated	
Carcinogenicity		Hazardous: calculated	
STOT-single exposure	INH	Hazardous: calculated	
STOT-repeated exposure	-	Hazardous: calculated	

Polycraft Polyfoam Rigid 145 Part B

Page: 7

Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

Section 12: Ecological information

Polycraft Polyfoam Rigid 145 Part B

12.1. Toxicity

Ecotoxicity values: No data available.

12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: React with Polycraft Polyfoam Rigid 145 Part A to give non hazardous foam or:- Transfer to a suitable container and arrange for collection by specialised disposal company.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

Transport class: This product does not require a classification for transport.

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Diisocyanate processes may have to be registered with the appropriate authority, agency or inspectorate as laid down in the (Environmental Protection) Pollution Prevention Control Regulations for the various parts of the United Kingdom. This product is classified under the Chemical (Hazard Information and Packaging) Regulations, (CHIP) (United Kingdom)

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture by the supplier. The obligation to register according to the REACh Regulations (EC) No. 1907/2006 does not apply to polymers.

Section 16: Other information

Page: 6

Polycraft Polyfoam Rigid 145 Part B

Other information

Other information: Mix only with Polycraft Polyfoam Rigid 145 Part A, do not decant into unlabelled containers. This safety data sheet is prepared in accordance with Commission Regulation (EU) No 2015/830.

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: H315: Causes skin irritation.

H317: May cause an allergic skin reaction. H319: Causes serious eye irritation.

H332: Harmful if inhaled.

H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled. H335: May cause respiratory irritation.

H351: Suspected of causing cancer < state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>.

H373: May cause damage to organs <or state all organs affected, if known> through prolonged or repeated exposure <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.