

# SAFETY DATA SHEET

## Polycraft CA800 Activator

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

**Product name** : Polycraft CA800 Activator

**Product number** : QL9811

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Identified uses** Activator.

#### 1.3. Details of the supplier of the safety data sheet

**Supplier** MB Fibreglass  
Unit 17 & 20 Abbey Business Park  
Mill Road  
Newtownabbey  
Co. Antrim  
BT36 7EE  
02890 861992

#### 1.4. Emergency telephone number

**Emergency telephone** : 02890 861992 (Business Hours)

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification

**Physical hazards** Aerosol 1 - H222, H229  
**Health hazards** Skin Irrit. 2 - H315 STOT SE 3 - H336  
**Environmental hazards** Aquatic Chronic 2 - H411

**Classification (67/548/EEC or 1999/45/EC)** F+; R12. Xi; R38. N; R51/53. R67

**Human health** Vapours and spray/mists in high concentrations are narcotic. See Section 11 for additional information on health hazards.

**Environmental** The product contains a substance which is toxic to aquatic organisms.

**Physicochemical** Containers can burst violently or explode when heated, due to excessive pressure build-up. The product is extremely flammable. Vapours may form explosive mixtures with air.

#### 2.2. Label elements

##### Pictogram



**Signal word**

Danger

##### Hazard statements

H222 Extremely flammable aerosol.  
H229 Pressurised container: may burst if heated  
H315 Causes skin irritation.  
H336 May cause drowsiness or dizziness.  
H411 Toxic to aquatic life with long lasting effects.

## Polycraft CA800 Activator

<b>Precautionary statements</b>	<p>P102 Keep out of reach of children.</p> <p>P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.</p> <p>P211 Do not spray on an open flame or other ignition source.</p> <p>P251 Do not pierce or burn, even after use.</p> <p>P261 Avoid breathing vapour/spray.</p> <p>P271 Use only outdoors or in a well-ventilated area.</p> <p>P280 Wear protective gloves/protective clothing/eye protection/face protection.</p> <p>P302+P352 IF ON SKIN: Wash with plenty of water.</p> <p>P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.</p> <p>P312 Call a POISON CENTER/doctor if you feel unwell.</p> <p>P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.</p>
<b>Contains</b>	<p>HYDROCARBONS, C6-C7, N-ALKANES, ISOALKANES, CYCLICS, &lt;5% N-HEXANE, HYDROCARBONS, C6 ISOALKANES &lt;5% N-HEXANE</p>
<b>Supplementary precautionary statements</b>	<p>P264 Wash contaminated skin thoroughly after handling.</p> <p>P273 Avoid release to the environment.</p> <p>P321 Specific treatment (see medical advice on this label).</p> <p>P332+P313 If skin irritation occurs: Get medical advice/attention.</p> <p>P362+P364 Take off contaminated clothing and wash it before reuse.</p> <p>P391 Collect spillage.</p> <p>P403+P233 Store in a well-ventilated place. Keep container tightly closed.</p> <p>P405 Store locked up.</p> <p>P501 Dispose of contents/container in accordance with national regulations.</p>

### 2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

### SECTION 3: Composition/information on ingredients

#### 3.2. Mixtures

<b>HYDROCARBONS, C6-C7, N-ALKANES, ISOALKANES, CYCLICS, &lt;5% N-HEXANE</b>	<b>30-60%</b>
CAS number: 64742-49-0	EC number: 921-024-6
	REACH registration number: 01-2119475514-35-XXXX
<b>Classification</b>	
Flam. Liq. 2 - H225	
Skin Irrit. 2 - H315	
STOT SE 3 - H336	
Asp. Tox. 1 - H304	
STOT SE 3 - H336	
Aquatic Chronic 2 - H411	
<b>PETROLEUM GASES, LIQUEFIED</b>	<b>10-30%</b>
CAS number: 68476-85-7	EC number: 270-704-2
<b>Classification</b>	
Flam. Gas 1 - H220	
Press. Gas, Compressed - H280	

## Polycraft CA800 Activator

<b>HYDROCARBONS, C6 ISOALKANES &lt;5% N-HEXANE</b>		<b>10-30%</b>
CAS number: 64742-49-0	EC number: 931-254-9	REACH registration number: 01-2119484651-34-XXXX

### Classification

Flam. Liq. 2 - H225  
 Skin Irrit. 2 - H315  
 STOT SE 3 - H336  
 Asp. Tox. 1 - H304  
 Aquatic Chronic 2 - H411

<b>N,N-DIMETHYL-P-TOLUIDINE</b>		<b>&lt;1%</b>
CAS number: 99-97-8	EC number: 202-805-4	

### Classification

Acute Tox. 3 - H301  
 Acute Tox. 3 - H311  
 Acute Tox. 3 - H331  
 STOT RE 2 - H373  
 Aquatic Chronic 3 - H412

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

<b>General information</b>	Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Get medical attention if any discomfort continues.
<b>Inhalation</b>	Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. If in doubt, get medical attention promptly.
<b>Ingestion</b>	Rinse mouth thoroughly with water. Remove person to fresh air and keep comfortable for breathing. Get medical attention.
<b>Skin contact</b>	Wash skin thoroughly with soap and water. Get medical attention promptly if symptoms occur after washing.
<b>Eye contact</b>	Remove any contact lenses and open eyelids wide apart. Rinse immediately with plenty of water. Continue to rinse for at least 15 minutes. Get medical attention promptly if symptoms occur after washing.
<b>Protection of first aiders</b>	First aid personnel should wear appropriate protective equipment during any rescue.

### 4.2. Most important symptoms and effects, both acute and delayed

**General information** See Section 11 for additional information on health hazards.

### 4.3. Indication of any immediate medical attention and special treatment needed

**Notes for the doctor** Treat symptomatically.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

**Suitable extinguishing media** Foam, carbon dioxide or dry powder.

### 5.2. Special hazards arising from the substance or mixture

## Polycraft CA800 Activator

**Specific hazards** Containers can burst violently or explode when heated, due to excessive pressure build-up.

### 5.3. Advice for firefighters

**Protective actions during firefighting** Use water to keep fire exposed containers cool and disperse vapours. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

**Personal precautions** Avoid inhalation of vapours and contact with skin and eyes. Ensure suitable respiratory protection is worn during removal of spillages in confined areas.

### 6.2. Environmental precautions

**Environmental precautions** Avoid discharge into drains.

### 6.3. Methods and material for containment and cleaning up

**Methods for cleaning up** Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. Absorb in vermiculite, dry sand or earth and place into containers.

### 6.4. Reference to other sections

**Reference to other sections** For personal protection, see Section 8. See Section 11 for additional information on health hazards. See Section 12 for additional information on ecological hazards. For waste disposal, see Section 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

**Usage precautions** Keep away from heat, sparks and open flame. Read and follow manufacturer's recommendations. When sprayed on a naked flame or any incandescent material the aerosol vapours can be ignited. Use suitable respiratory protection if ventilation is inadequate.

**Advice on general occupational hygiene** Wash promptly with soap and water if skin becomes contaminated. Do not eat, drink or smoke when using this product.

### 7.2. Conditions for safe storage, including any incompatibilities

**Storage precautions** Protect from freezing and direct sunlight. Store in a dry place. Do not store near heat sources or expose to high temperatures. Keep away from heat, sparks and open flame.

### 7.3. Specific end use(s)

**Specific end use(s)** The identified uses for this product are detailed in Section 1.2.

## SECTION 8: Exposure Controls/personal protection

### 8.1. Control parameters

#### Occupational exposure limits

#### **PETROLEUM GASES, LIQUEFIED**

Long-term exposure limit (8-hour TWA): WEL 1000 ppm 1750 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): WEL 1250 ppm 2180 mg/m<sup>3</sup>

WEL = Workplace Exposure Limit

**HYDROCARBONS, C6-C7, N-ALKANES, ISOALKANES, CYCLICS, <5% N-HEXANE (CAS: 64742-49-0)**

## Polycraft CA800 Activator

<b>DNEL</b>	Consumer - Oral; Long term systemic effects: 699 mg/kg/day
	Workers - Oral; Long term systemic effects: 773 mg/kg/day
	Workers - Dermal; Long term systemic effects: 773 mg/kg/day
	Consumer - Dermal; Long term systemic effects: 699 mg/kg/day
	Consumer - Inhalation; Long term systemic effects: 608 mg/m <sup>3</sup>

### HYDROCARBONS, C6 ISOALKANES <5% N-HEXANE (CAS: 64742-49-0)

<b>DNEL</b>	Consumer - Oral; Long term systemic effects: 1301 mg/kg/day
	Consumer - Dermal; Long term systemic effects: 1377 mg/kg/day
	Workers - Dermal; Long term systemic effects: 13964 mg/kg/day
	Consumer - Inhalation; Long term systemic effects: 1131 mg/m <sup>3</sup>
	Workers - Inhalation; Long term systemic effects: 5306 mg/m <sup>3</sup>

### 8.2. Exposure controls

<b>Eye/face protection</b>	Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible.
<b>Hand protection</b>	No specific requirements are anticipated under normal conditions of use.
<b>Other skin and body protection</b>	Wear suitable protective equipment for prolonged exposure and/or high concentrations of vapours, spray or mist.
<b>Respiratory protection</b>	No specific recommendations. If ventilation is inadequate, suitable respiratory protection must be worn.

## **SECTION 9: Physical and Chemical Properties**

### 9.1. Information on basic physical and chemical properties

<b>Appearance</b>	Aerosol.
<b>Colour</b>	Clear.
<b>Odour</b>	Solvents
<b>Odour threshold</b>	No information available.
<b>pH</b>	No information available.
<b>Melting point</b>	No information available.
<b>Initial boiling point and range</b>	-41 (-41 TO 215)°C @
<b>Flash point</b>	-40°C CC (Closed cup).
<b>Evaporation rate</b>	No information available.
<b>Evaporation factor</b>	No information available.
<b>Flammability (solid, gas)</b>	No information available.
<b>Upper/lower flammability or explosive limits</b>	Lower flammable/explosive limit: 1.0 % Upper flammable/explosive limit: 9.5 %
<b>Vapour pressure</b>	No information available.
<b>Vapour density</b>	No information available.
<b>Relative density</b>	0.651
<b>Solubility(ies)</b>	Insoluble in water.
<b>Partition coefficient</b>	No information available.

## Polycraft CA800 Activator

<b>Auto-ignition temperature</b>	413°C
<b>Decomposition Temperature</b>	No information available.
<b>Viscosity</b>	No information available.
<b>Explosive properties</b>	No information available.
<b>Oxidising properties</b>	No information available.

### 9.2. Other information

<b>Other information</b>	None.
--------------------------	-------

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

<b>Reactivity</b>	No test data specifically related to reactivity available for this product or its ingredients.
-------------------	--

### 10.2. Chemical stability

<b>Stability</b>	The product may not be stable under some conditions of storage or use.
------------------	--

### 10.3. Possibility of hazardous reactions

<b>Possibility of hazardous reactions</b>	None known.
---	-------------

### 10.4. Conditions to avoid

<b>Conditions to avoid</b>	Avoid heat, flames and other sources of ignition. Avoid exposing aerosol containers to high temperatures or direct sunlight.
----------------------------	--

### 10.5. Incompatible materials

<b>Materials to avoid</b>	None known.
---------------------------	-------------

### 10.6. Hazardous decomposition products

<b>Hazardous decomposition products</b>	None at ambient temperatures.
---	-------------------------------

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

#### Acute toxicity - oral

<b>ATE oral (mg/kg)</b>	25,000.0
-------------------------	----------

#### Acute toxicity - dermal

<b>ATE dermal (mg/kg)</b>	75,000.0
---------------------------	----------

#### Acute toxicity - inhalation

<b>ATE inhalation (vapours mg/l)</b>	750.0
--------------------------------------	-------

<b>Inhalation</b>	Vapours in high concentrations are narcotic. Vapours may cause headache, fatigue, dizziness and nausea.
<b>Skin contact</b>	Causes skin irritation.
<b>Eye contact</b>	Vapour or spray in the eyes may cause irritation and smarting.
<b>Acute and chronic health hazards</b>	No known chronic or acute health risks.

## Polycraft CA800 Activator

Route of entry Skin and/or eye contact Inhalation

### Toxicological information on ingredients.

#### HYDROCARBONS, C6-C7, N-ALKANES, ISOALKANES, CYCLICS, <5% N-HEXANE

##### Acute toxicity - oral

Acute toxicity oral (LD<sub>50</sub>  
mg/kg) 5,001.0

Species Rat

ATE oral (mg/kg) 5,001.0

##### Acute toxicity - dermal

Acute toxicity dermal (LD<sub>50</sub>  
mg/kg) 2,001.0

Species Rabbit

ATE dermal (mg/kg) 2,001.0

#### HYDROCARBONS, C6 ISOALKANES <5% N-HEXANE

##### Acute toxicity - oral

Acute toxicity oral (LD<sub>50</sub>  
mg/kg) 5,001.0

Species Rat

ATE oral (mg/kg) 5,001.0

##### Acute toxicity - dermal

Acute toxicity dermal (LD<sub>50</sub>  
mg/kg) 2,001.0

Species Rabbit

ATE dermal (mg/kg) 2,001.0

##### Acute toxicity - inhalation

Acute toxicity inhalation  
(LC<sub>50</sub> vapours mg/l) 21.0

Species Rat

ATE inhalation (vapours  
mg/l) 21.0

#### N,N-DIMETHYL-P-TOLUIDINE

##### Acute toxicity - oral

Acute toxicity oral (LD<sub>50</sub>  
mg/kg) 1,650.0

Species Rat

ATE oral (mg/kg) 100.0

##### Acute toxicity - inhalation

## Polycraft CA800 Activator

Acute toxicity inhalation (LC <sub>50</sub> vapours mg/l)	1.4
Species	Rat
ATE inhalation (vapours mg/l)	3.0

### SECTION 12: Ecological Information

#### 12.1. Toxicity

##### Ecological information on ingredients.

##### HYDROCARBONS, C6-C7, N-ALKANES, ISOALKANES, CYCLICS, <5% N-HEXANE

Acute toxicity - fish	LOEC, : 1-10 mg/l, Fish
Acute toxicity - aquatic plants	LOEC, : 10-100 mg/l, Algae
Acute toxicity - microorganisms	LOEC, : 1-10 mg/l, Activated sludge

##### HYDROCARBONS, C6 ISOALKANES <5% N-HEXANE

Acute toxicity - fish	LOEC, : 10-100 mg/l, Fish
Acute toxicity - aquatic plants	LOEC, : 10-100 mg/l, Algae

##### N,N-DIMETHYL-P-TOLUIDINE

Acute toxicity - fish	LC <sub>50</sub> , 96 hours: 46-52 mg/l, Pimephales promelas (Fat-head Minnow)
-----------------------	--

#### 12.2. Persistence and degradability

Persistence and degradability No data available.

#### 12.3. Bioaccumulative potential

Partition coefficient No information available.

#### 12.4. Mobility in soil

Mobility No data available

#### 12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB  
assessment This product does not contain any substances classified as PBT or vPvB.

#### 12.6. Other adverse effects

Other adverse effects None known.

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

General information	Dispose of waste product or used containers in accordance with local regulations
Disposal methods	Containers should be thoroughly emptied before disposal because of the risk of an explosion. Do not pierce or burn, even after use.



## Polycraft CA800 Activator

### SECTION 14: Transport information

#### 14.1. UN number

UN No. (ADR/RID)	1950
UN No. (IMDG)	1950
UN No. (ICAO)	1950
UN No. (ADN)	1950

#### 14.2. UN proper shipping name

Proper shipping name (ADR/RID)	AEROSOLS
Proper shipping name (IMDG)	AEROSOLS
Proper shipping name (ICAO)	AEROSOLS, FLAMMABLE
Proper shipping name (ADN)	AEROSOLS

#### 14.3. Transport hazard class(es)

ADR/RID class	2.1
ADR/RID classification code	5F
ADR/RID label	2.1
IMDG class	2.1
ICAO class/division	2.1
ADN class	2.1

#### Transport labels



#### 14.4. Packing group

Not applicable.

#### 14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant



#### 14.6. Special precautions for user

EmS	F-D, S-U
ADR transport category	2
Tunnel restriction code	(D)

#### 14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

## Polycraft CA800 Activator

### SECTION 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

<b>National regulations</b>	The Aerosol Dispensers Regulations 2009 (SI 2009 No. 2824).
<b>EU legislation</b>	Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended). Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended). Council Directive of 20 May 1975 on the approximation of the laws of the Member States relating to aerosol dispensers (75/324/EEC) (as amended).

#### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

### SECTION 16: Other information

<b>Revision date</b>	20/01/2016
<b>Revision</b>	2
<b>Supersedes date</b>	30/07/2014
<b>SDS number</b>	4864
<b>Hazard statements in full</b>	H220 Extremely flammable gas. H222 Extremely flammable aerosol. H225 Highly flammable liquid and vapour. H229 Pressurised container: may burst if heated H280 Contains gas under pressure; may explode if heated. H301 Toxic if swallowed. H304 May be fatal if swallowed and enters airways. H311 Toxic in contact with skin. H315 Causes skin irritation. H331 Toxic if inhaled. H336 May cause drowsiness or dizziness. H373 May cause damage to organs through prolonged or repeated exposure. H411 Toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.