


Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Regulation (EU) No. 2020/878 - United Kingdom: Northern Ireland

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name :  Hempel's High Protect II Base
Product identity : 3578913700
Product type : epoxy paint (base for 2-component product)

1.2 Relevant identified uses of the substance or mixture and uses advised against

Field of application : used only as part of two- or multi component products
Ready-for-use mixture : 35780 = 35789 3 vol. / 95078 2 vol.
Identified uses : Consumer applications, Professional applications.

1.3 Details of the supplier of the safety data sheet

Company details : Hempel UK Ltd
Berwyn House, The Pavilions
Llantarnam Park
Cwmbran
South Wales NP44 3FD
Telephone: 01633 833600
hempel@hempel.com

1.4 Emergency telephone number

Emergency telephone number (with hours of operation)

01633 833600 (08.00 - 17.00)
See Section 4 of the safety data sheet (first aid measures).



Date of issue : 15 December 2021
Date of previous issue : 2 July 2020.

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture


Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

 Skin Irrit. 2, H315 SKIN CORROSION/IRRITATION
 Eye Irrit. 2, H319 SERIOUS EYE DAMAGE/EYE IRRITATION
Skin Sens. 1, H317 SKIN SENSITISATION
Aquatic Chronic 2, H411 LONG-TERM (CHRONIC) AQUATIC HAZARD

See Section 11 for more detailed information on health effects and symptoms.




2.2 Label elements

Hazard pictograms :




Signal word : Warning
Hazard statements : H315 - Causes skin irritation.
H317 - May cause an allergic skin reaction.
H319 - Causes serious eye irritation.
H411 - Toxic to aquatic life with long lasting effects.

Precautionary statements :

General :  Keep out of reach of children. If medical advice is needed, have product container or label at hand.
Prevention :  Wear protective gloves. Wear eye or face protection. Avoid release to the environment. Avoid breathing vapour. Wash thoroughly after handling.
Response :  Collect spillage. Take off contaminated clothing and wash it before reuse. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice or attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention.
Disposal : Dispose of contents and container in accordance with all local, regional, national and international regulations.

SECTION 2: Hazards identification

Hazardous ingredients :  Bisphenol A-(epichlorhydrin) epoxy resin MW =< 700
formaldehyde, polymer with (chloromethyl)oxirane and phenol
1,6-hexanediol diglycidylether
oxirane, mono[(C12-14-alkyloxy)methyl] derivs.

Supplemental label elements : Contains epoxy constituents. May produce an allergic reaction.

Special packaging requirements

Containers to be fitted with child-resistant fastenings : Not applicable.

Tactile warning of danger : Not applicable.


2.3 Other hazards

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

Other hazards which do not result in classification : None known.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Product/ingredient name	Identifiers	%	Regulation (EC) No. 1272/2008 [CLP]	Type
 Bisphenol A-(epichlorhydrin) epoxy resin MW =< 700	REACH #: 01-2119456619-26 EC: 500-033-5 CAS: 1675-54-3 Index: 603-074-00-8	≥25 - ≤50	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 2, H411	- [1]
formaldehyde, polymer with (chloromethyl)oxirane and phenol	REACH #: 01-2119454392-40 EC: 500-006-8 CAS: 9003-36-5	≥10 - ≤25	Skin Irrit. 2, H315 Skin Sens. 1, H317 Aquatic Chronic 2, H411	- [1]
1,6-hexanediol diglycidylether	REACH #: 01-2119463471-41 EC: 240-260-4 CAS: 933999-84-9	≥5 - ≤10	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 3, H412	- [1]
oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	REACH #: 01-2119485289-22 EC: 271-846-8 CAS: 68609-97-2 Index: 603-103-00-4	≥5 - ≤10	Skin Irrit. 2, H315 Skin Sens. 1, H317	- [1]
bis(isopropyl)naphthalene	REACH #: 01-2119565150-48 EC: 254-052-6 CAS: 38640-62-9	≥5 - ≤10	Asp. Tox. 1, H304 Aquatic Chronic 1, H410 (M=1)	- [1]
amide wax	REACH #: 01-0000017860-69 EC: 432-430-3	≥1 - ≤3	Aquatic Chronic 4, H413	- [1]
C12-14 alcohols	EC: 279-420-3 CAS: 80206-82-2	≤0.3	Skin Irrit. 2, H315 Aquatic Acute 1, H400 (M=1) See Section 16 for the full text of the H statements declared above.	- [1]

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Type

- [1] Substance classified with a health or environmental hazard
- [2] Substance with a workplace exposure limit, see section 8.
- [3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII
- [4] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII
- [5] Substance of equivalent concern
- [6] Additional disclosure due to company policy

SECTION 4: First aid measures

4.1 Description of first aid measures

General : In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.
If breathing is irregular, drowsiness, loss of consciousness or cramps: Call 112 and give immediate treatment (first aid).

Eye contact : Check for and remove any contact lenses. Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Seek immediate medical attention.

Inhalation : Remove to fresh air. Keep person warm and at rest. If unconscious, place in recovery position and seek medical advice.

Skin contact : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.

SECTION 4: First aid measures

Ingestion :	If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do not induce vomiting unless directed to do so by medical personnel. Lower the head so that vomit will not re-enter the mouth and throat.
Protection of first-aiders :	No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

Potential acute health effects

Eye contact :	Causes serious eye irritation.
Inhalation :	No known significant effects or critical hazards.
Skin contact :	Causes skin irritation. May cause an allergic skin reaction.
Ingestion :	No known significant effects or critical hazards.

Over-exposure signs/symptoms

Eye contact :	Adverse symptoms may include the following: pain or irritation watering redness
Inhalation :	No specific data.
Skin contact :	Adverse symptoms may include the following: irritation redness
Ingestion :	No specific data.

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician :	Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Specific treatments :	No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Extinguishing media :	Recommended: alcohol resistant foam, CO ₂ , powders, water spray. Not to be used : waterjet.
-----------------------	--

5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture :	In a fire or if heated, a pressure increase will occur and the container may burst. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
Hazardous combustion products :	Decomposition products may include the following materials: carbon oxides halogenated compounds metal oxide/oxides

5.3 Advice for firefighters

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard. Cool closed containers exposed to fire with water. Do not release runoff from fire to drains or watercourses. Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Refer to protective measures listed in sections 7 and 8. No action shall be taken involving any personal risk or without suitable training.

6.2 Environmental precautions

Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

SECTION 6: Accidental release measures

6.3 Methods and material for containment and cleaning up

Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Contaminated absorbent material may pose the same hazard as the spilt product.

6.4 Reference to other sections

See Section 1 for emergency contact information.
See Section 8 for information on appropriate personal protective equipment.
See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Contains epoxy constituents. Avoid all possible skin contact with epoxy and amine containing products, they may cause allergic reactions. Avoid inhalation of vapour, dust and spray mist. Avoid contact with skin and eyes. Eating, drinking and smoking should be prohibited in area where this material is handled, stored and processed. Appropriate personal protective equipment: see Section 8. Always keep in containers made from the same material as the original one.

7.2 Conditions for safe storage, including any incompatibilities


Store in accordance with local regulations. Store in a cool, well-ventilated area away from incompatible materials and ignition sources. Keep out of the reach of children. Keep away from: Oxidizing agents, strong alkalis, strong acids. No smoking. Prevent unauthorized access. Containers that are opened must be carefully resealed and kept upright to prevent leakage.

7.3 Specific end use(s)

See separate Product Data Sheet for recommendations or industrial sector specific solutions.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Product/ingredient name	Exposure limit values
 exposure limit value known.	

Recommended monitoring procedures

If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

Derived effect levels

Not applicable.

Predicted effect concentrations

Not applicable.

8.2 Exposure controls


Appropriate engineering controls

Arrange sufficient ventilation by local exhaust ventilation and good general ventilation to keep the airborne concentrations of vapors or dust lowest possible and below their respective threshold limit value. Ensure that eyewash stations and safety showers are proximal to the work-station location.

Individual protection measures

General : Gloves must be worn for all work that may result in soiling. Apron/coveralls/protective clothing must be worn when soiling is so great that regular work clothes do not adequately protect skin against contact with the product. Safety eyewear should be used when there is a likelihood of exposure.

SECTION 8: Exposure controls/personal protection



Hygiene measures :	Wash hands, forearms, and face thoroughly after handling compounds and before eating, smoking, using lavatory, and at the end of day.
Eye/face protection :	Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.
Hand protection :	<p>Wear chemical-resistant gloves (tested to EN374) in combination with 'basic' employee training. The quality of the chemical-resistant protective gloves must be chosen as a function of the specific workplace concentrations and quantity of hazardous substances.</p> <p>Since the actual work situation is unknown. Supplier of gloves should be contacted in order to find the appropriate type. Below listed glove(s) should be regarded as generic advice:</p> <p>Short term exposure: natural rubber (latex) Recommended: Silver Shield / Barrier / 4H gloves, butyl rubber, Viton® May be used: polyvinyl alcohol (PVA), polyvinyl chloride (PVC), nitrile rubber, neoprene rubber</p>
Body protection :	Personal protective equipment for the body should be selected based on the task being performed and the risks involved handling this product.
Respiratory protection :	Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Wear appropriate respirator when ventilation is inadequate. Be sure to use approved/certified respirator or equivalent. It is not possible to specify precise filter type, since the actual work situation is unknown. Supplier of respirators should be contacted in order to find the appropriate filter.

Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state :	Liquid.
Colour :	Grey.
Odour :	Amine-like.
pH :	Testing not relevant or not possible due to nature of the product.
Melting point/freezing point :	-16°C This is based on data for the following ingredient: bisphenol A-(epichlorhydrin) epoxy resin MW = < 700
Boiling point/boiling range :	Testing not relevant or not possible due to nature of the product.
Flash point :	Closed cup: 143°C (289.4°F)
Evaporation rate :	Testing not relevant or not possible due to nature of the product.
Flammability :	Not available.
Lower and upper explosive (flammable) limits :	No specific data.
Vapour pressure :	0 kPa This is based on data for the following ingredient: bisphenol A-(epichlorhydrin) epoxy resin MW = < 700
Vapour density :	Testing not relevant or not possible due to nature of the product.
Specific gravity :	1.26 g/cm ³
Solubility(ies) :	Insoluble in the following materials: cold water and hot water.
Partition coefficient (LogKow) :	Testing not relevant or not possible due to nature of the product.
Auto-ignition temperature :	Testing not relevant or not possible due to nature of the product.
Decomposition temperature :	Testing not relevant or not possible due to nature of the product.
Viscosity :	Aspiration hazard (H304) Not classified. Testing not relevant due to nature of the product.
Explosive properties :	Testing not relevant or not possible due to nature of the product.
Oxidising properties :	Testing not relevant or not possible due to nature of the product.

SECTION 9: Physical and chemical properties

9.2 Other information

Solvent(s) % by weight :	Weighted average: 1 %
Water % by weight :	Weighted average: 0 %
VOC content :	11.1 g/l
VOC content, Ready-for-use mixture :	34.1 g/l
TOC Content :	Weighted average: 8 g/l
Solvent Gas :	Weighted average: 0.002 m³/l

SECTION 10: Stability and reactivity

10.1 Reactivity

No specific test data related to reactivity available for this product or its ingredients.

10.2 Chemical stability

The product is stable.

10.3 Possibility of hazardous reactions

Under normal conditions of storage and use, hazardous reactions will not occur.

10.4 Conditions to avoid

No specific data.

10.5 Incompatible materials

10.6 Hazardous decomposition products

When exposed to high temperatures (i.e. in case of fire) harmful decomposition products may be formed:

Decomposition products may include the following materials: carbon oxides halogenated compounds metal oxide/oxides

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Epoxy and amine containing products can cause skin disorders such as allergic eczema. The allergy may arise after only a short exposure period.

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Bisphenol A-(epichlorhydrin) epoxy resin MW =< 700	LD50 Dermal	Rabbit	>2000 mg/kg	-
	LD50 Dermal	Rat	>2000 mg/kg	-
	LD50 Oral	Rat	>2000 mg/kg	-
formaldehyde, polymer with (chloromethyl)oxirane and phenol	LD50 Oral	Rabbit	>2000 mg/kg	-
	LD50 Dermal	Rabbit	>2000 mg/kg	-
1,6-hexanediol diglycidylether	LD50 Oral	Rat	>2000 mg/kg	-
	LD50 Dermal	Rat	>2000 mg/kg	-
oxirane, mono[(C12-14-alkyloxy) methyl] derivs.	LD50 Oral	Rat	2190 mg/kg	-
	LD50 Dermal	Rat	>4500 mg/kg	-
bis(isopropyl)naphthalene	LD50 Oral	Rat	>5000 mg/kg	-
	LD50 Dermal	Rat	>4000 mg/kg	-
	LD50 Oral	Rat	>4000 mg/kg	-

Acute toxicity estimates

Product/ingredient name	Oral mg/kg	Dermal mg/kg	Inhalation (gases) ppm	Inhalation (vapours) mg/l	Inhalation (dusts and mists) mg/l
1,6-hexanediol diglycidylether	2190				

Irritation/Corrosion

SECTION 11: Toxicological information

Product/ingredient name	Result	Species	Score	Exposure
Bisphenol A-(epichlorhydrin) epoxy resin MW =< 700 formaldehyde, polymer with (chloromethyl)oxirane and phenol 1,6-hexanediol diglycidylether oxirane, mono[(C12-14-alkyloxy) methyl] derivs.	Eyes - Mild irritant	Rabbit	-	24 hours 500 microliters
	Skin - Mild irritant	Rabbit	-	
	Skin - Mild irritant	Rabbit	-	
	Skin - Irritant	Rabbit	-	
	Eyes - Irritant	Rabbit	-	
	Eyes - Mild irritant	Rabbit	-	
	Skin - Moderate irritant	Rabbit	-	

Sensitiser

Product/ingredient name	Route of exposure	Species	Result
Bisphenol A-(epichlorhydrin) epoxy resin MW =< 700 1,6-hexanediol diglycidylether oxirane, mono[(C12-14-alkyloxy) methyl] derivs.	skin	Guinea pig	Sensitising
	skin	Guinea pig	Sensitising
	skin	Guinea pig	Sensitising

Mutagenic effects

No known significant effects or critical hazards.

Carcinogenicity

No known significant effects or critical hazards.

Reproductive toxicity

No known significant effects or critical hazards.

Teratogenic effects

No known significant effects or critical hazards.

Specific target organ toxicity (single exposure)

Product/ingredient name	Category	Route of exposure	Target organs
No known data available in our database.			

Specific target organ toxicity (repeated exposure)

Product/ingredient name	Category	Route of exposure	Target organs
No known data available in our database.			

Aspiration hazard

Product/ingredient name	Result
bis(isopropyl)naphthalene	ASPIRATION HAZARD - Category 1

Information on likely routes of exposure

Routes of entry anticipated: Oral, Dermal, Inhalation.

Potential chronic health effects

Sensitisation : Contains bisphenol A-(epichlorhydrin) epoxy resin MW =< 700, formaldehyde, polymer with (chloromethyl)oxirane and phenol, 1,6-hexanediol diglycidylether, oxirane, mono[(C12-14-alkyloxy) methyl] derivs.. May produce an allergic reaction.

11.2 Information on other hazards

Endocrine disrupting properties : No known data available in our database.

Other information : No additional known significant effects or critical hazards.

SECTION 12: Ecological information

12.1 Toxicity

Do not allow to enter drains or watercourses. Toxic to aquatic life with long lasting effects.

Product/ingredient name	Result	Species	Exposure
Bisphenol A-(epichlorhydrin) epoxy resin MW =< 700	Acute EC50 >11 mg/l	Algae	72 hours
	Acute EC50 1.8 mg/l Acute LC50 2 mg/l Acute EC50 2.54 mg/l	Daphnia Fish Fish	48 hours 96 hours 96 hours
formaldehyde, polymer with (chloromethyl)oxirane and phenol	Acute LC50 1.8 mg/l Acute LC50 2.55 mg/l	Algae Daphnia	72 hours 48 hours
	Acute EC50 23.1 mg/l Acute LC50 47 mg/l Acute LC50 30 mg/l	Algae Daphnia Fish	48 hours 48 hours 96 hours
1,6-hexanediol diglycidylether	Acute IC50 843.75 mg/l	Algae	72 hours
oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	Acute LC50 5000 mg/l Acute LC50 1.7 mg/l Acute NOEC 0.013 mg/l	Fish Daphnia Daphnia	96 hours 48 hours 21 days

12.2 Persistence and degradability

Product/ingredient name	Test	Result	Dose	Inoculum
Bisphenol A-(epichlorhydrin) epoxy resin MW =< 700	OECD 302B Inherent Biodegradability: Zahn-Wellens/EMPA Test	12 % - Not readily - 28 days	-	-
	OECD 301B Ready Biodegradability - CO2 Evolution Test	16 % - Not readily - 28 days	-	-
formaldehyde, polymer with (chloromethyl)oxirane and phenol	OECD 301D Ready Biodegradability - Closed Bottle Test	47 % - Inherent - 28 days	2 mg/l	-
	-	87 % - Readily - 28 days	-	-
1,6-hexanediol diglycidylether	-	<70 % - Not readily - 28 days	-	-
oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	-	-	-	-
amide wax	-	-	-	-

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
Bisphenol A-(epichlorhydrin) epoxy resin MW =< 700	-	-	Not readily
formaldehyde, polymer with (chloromethyl)oxirane and phenol	-	-	Not readily
1,6-hexanediol diglycidylether	-	-	Inherent
oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	-	-	Readily
amide wax	-	-	Not readily

12.3 Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
Bisphenol A-(epichlorhydrin) epoxy resin MW =< 700	2.64 - 3.78	31	low
formaldehyde, polymer with (chloromethyl)oxirane and phenol	2.7	150	low
1,6-hexanediol diglycidylether	0.822	3.57	low
oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	3.77	160 - 263	low
bis(isopropyl)naphthalene	6.081	1800 - 6400	high

12.4 Mobility in soil

Soil/water partition coefficient (K_{oc}) : No known data available in our database.

Mobility : No known data available in our database.

12.5 Results of PBT and vPvB assessment

Product/ingredient name	PBT	P	B	T	vPvB	vP	vB
This mixture does not contain any substances that are assessed to be a PBT or a vPvB.							

12.6 Endocrine disrupting properties

SECTION 12: Ecological information

No known data available in our database.

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

The generation of waste should be avoided or minimised wherever possible. Residues of the product is listed as hazardous waste. Dispose of according to all state and local applicable regulations. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

European waste catalogue no. (EWC) is given below.







European waste catalogue (EWC) : 08 01 11*

Packaging

The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

SECTION 14: Transport information

Transport may take place according to national regulation or ADR for transport by road, RID for transport by train, IMDG for transport by sea, IATA for transport by air.

	14.1 UN / ID no.	14.2 Proper shipping name	14.3 Transport hazard class(es)	14.4 PG*	14.5 Env*	Additional information
ADR/RID Class	UN3082	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (bisphenol A-(epichlorhydrin) epoxy resin MW =< 700)	9  	III	Yes.	This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.
IMDG Class	UN3082	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.. (bisphenol A-(epichlorhydrin) epoxy resin MW =< 700)	9  	III	Yes.	This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8. Emergency schedules F-A, S-F
IATA Class	UN3082	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (bisphenol A-(epichlorhydrin) epoxy resin MW =< 700)	9  	III	Yes.	This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 5.0.2.4.1, 5.0.2.6.1.1 and 5.0.2.8.

PG* : Packing group

Env.* : Environmental hazards

14.6 Special precautions for user

Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH) Annex XIV - List of substances subject to authorisation - Substances of very high concern

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Not applicable.

Other EU regulations

Seveso category This product is controlled under the Seveso III Directive.

Seveso category
E2: Hazardous to the aquatic environment - Chronic 2

15.2 Chemical safety assessment

Consumer use: Chemical Safety Assessments for this product are either complete or not applicable.

SECTION 16: Other information

Abbreviations and acronyms :

ATE = Acute Toxicity Estimate
 CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
 EUH statement = CLP-specific Hazard statement
 RRN = REACH Registration Number
 DNEL = Derived No Effect Level
 PNEC = Predicted No Effect Concentration

Full text of abbreviated H statements :

H304 May be fatal if swallowed and enters airways.
 H315 Causes skin irritation.
 H317 May cause an allergic skin reaction.
 H319 Causes serious eye irritation.
 H400 Very toxic to aquatic life.
 H410 Very toxic to aquatic life with long lasting effects.
 H411 Toxic to aquatic life with long lasting effects.
 H412 Harmful to aquatic life with long lasting effects.
 H413 May cause long lasting harmful effects to aquatic life.

Full text of classifications [CLP/GHS] :

Aquatic Acute 1 SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1
 Aquatic Chronic 1 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1
 Aquatic Chronic 2 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2
 Aquatic Chronic 3 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3
 Aquatic Chronic 4 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 4
 Asp. Tox. 1 ASPIRATION HAZARD - Category 1
 Eye Irrit. 2 SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2
 Skin Irrit. 2 SKIN CORROSION/IRRITATION - Category 2
 Skin Sens. 1 SKIN SENSITISATION - Category 1

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
SKIN CORROSION/IRRITATION	Calculation method
SERIOUS EYE DAMAGE/EYE IRRITATION	Calculation method
SKIN SENSITISATION	Calculation method
LONG-TERM (CHRONIC) AQUATIC HAZARD	Calculation method

Notice to reader

Indicates information that has changed from previously issued version.

The information contained in this safety data sheet is based on the present state of knowledge and EU and national legislation. It provides guidance on health, safety and environmental aspects for handling the product in a safe way and should not be construed as any guarantee of the technical performance or suitability for particular applications.

It is always the duty of the user/employer to ascertain that the work is planned and carried out in accordance with the national regulations.

This document is intended to communicate the conditions of safe use for the product and should always be read in combination with the product's Safety Data Sheet and labels.

General description of the process covered

Indoor or outdoor spray painting by professionals or with brush, roller, putty knife, dipping etc. with good general room ventilation.

This safe use information is linked to : Professional spray painting and/or low-energy painting, local effect - Level II
Skin Sens. 1, Eye Irrit. 2 , Asp. Tox. 1 or Solvent.

Sector(s) of use : Industrial uses - Professional uses

Product category(ies) : Coatings and paints, thinners, paint removers

Operational conditions

Place of use : Indoor or outdoor use

Risk management measures (RMM)

Contributing activity	Process category (ies)	Maximum duration	Ventilation		Respiratory	Eye	Hands
			Type and air changes per hour				
Preparation of material for application	PROC05	More than 4 hours	Good general room ventilation - Outdoors	3 - 5	None	Use eye protection according to EN 166.	Wear suitable gloves tested to EN374.
Loading of application equipment and handling of coated parts before curing	PROC08a	More than 4 hours	Good general room ventilation - Outdoors	3 - 5	None	Use eye protection according to EN 166.	Wear suitable gloves tested to EN374.
Professional application of coatings by brush or roller	PROC10	More than 4 hours	Good general room ventilation - Outdoors	3 - 5	None	Use eye protection according to EN 166.	Wear suitable gloves tested to EN374.
Professional application of coatings by spraying	PROC11	More than 4 hours	Good general room ventilation - Outdoors	3 - 5	Wear a respirator conforming to EN140 with an assigned protection factor of at least 10.	Use eye protection according to EN 166.	Wear suitable gloves tested to EN374.
Film formation - force drying, stoving and other technologies	PROC04	More than 4 hours	Good general room ventilation - Outdoors	3 - 5	None	None	None
Cleaning	PROC05	More than 4 hours	Good general room ventilation - Outdoors	3 - 5	None	Use eye protection according to EN 166.	Wear suitable gloves tested to EN374.
Waste management	PROC08a	More than 4 hours	Good general room ventilation - Outdoors	3 - 5	None	Use eye protection according to EN 166.	Wear suitable gloves tested to EN374.

See chapter 8 of this Safety Data Sheet for specifications.

