



## SAFETY DATA SHEET

POLYESTER EASY SAND PRIMER/ POLYESTER HIGH  
BUILD BASE PRIMER/ FOUNDATION PRIMER

Page: 1

Compilation date: 09/07/2015

Revision No: 3

### Section 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

**Product name:** POLYESTER EASY SAND PRIMER/ POLYESTER HIGH BUILD BASE PRIMER/  
FOUNDATION PRIMER

**Product code:** PLQ04/PLQ05/PLQ06

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### 1.3. Details of the supplier of the safety data sheet

**Company name:** Llewellyn Ryland Ltd

Haden Street

Birmingham

B12 9DB

United Kingdom

**Tel:** +44 (0)121 440 2284

**Fax:** +44 (0)121 440 0281

**Email:** [technical@llewellyn-ryland.co.uk](mailto:technical@llewellyn-ryland.co.uk)

#### 1.4. Emergency telephone number

**Emergency tel:** +44 (0)121 440 2284  
(office hours only)

### Section 2: Hazards identification

#### 2.1. Classification of the substance or mixture

**Classification under CLP:** Flam. Liq. 2: H225; Eye Irrit. 2: H319; Repr. 2: H361d; Skin Irrit. 2: H315; STOT RE 1:  
H372; -: EUH208

**Most important adverse effects:** Contains cobalt bis(2-ethylhexanoate). May produce an allergic reaction. Highly flammable liquid and vapour. Causes skin irritation. Causes serious eye irritation. Suspected of damaging the unborn child. Causes damage to organs through prolonged or repeated exposure.

#### 2.2. Label elements

**Label elements:**

**Hazard statements:** EUH208: Contains cobalt bis(2-ethylhexanoate). May produce an allergic reaction.

H225: Highly flammable liquid and vapour.

H315: Causes skin irritation.

H319: Causes serious eye irritation.

H361d: Suspected of damaging the unborn child.

H372: Causes damage to organs through prolonged or repeated exposure.

[cont...]

# SAFETY DATA SHEET

POLYESTER EASY SAND PRIMER/ POLYESTER HIGH  
BUILD BASE PRIMER/ FOUNDATION PRIMER

Page: 2

**Signal words:** Danger

**Hazard pictograms:** GHS02: Flame

GHS07: Exclamation mark

GHS08: Health hazard



**Precautionary statements:** P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P260: Do not breathe dust/fumes/gas/mist/vapours/spray.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P302+352: IF ON SKIN: Wash with plenty of water/.

## 2.3. Other hazards

**Other hazards:** In use, may form flammable / explosive vapour-air mixture.

**PBT:** This product is not identified as a PBT/vPvB substance.

## Section 3: Composition/information on ingredients

### 3.2. Mixtures

#### Hazardous ingredients:

STYRENE - REACH registered number(s): 01-2119457861-32

EINECS	CAS	PBT / WEL	CLP Classification	Percent
202-851-5	100-42-5	-	Flam. Liq. 3: H226; Repr. 2: H361d; Acute Tox. 4: H332; STOT RE 1: H372; Skin Irrit. 2: H315; Eye Irrit. 2: H319	10-30%

ETHYL ACETATE - REACH registered number(s): 01-2119475103-46

205-500-4	141-78-6	-	Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336; -: EUH066	1-10%
-----------	----------	---	---	-------

ACETONE

200-662-2	67-64-1	-	Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336; -: EUH066	1-10%
-----------	---------	---	---	-------

LOW BOILING POINT HYDROGEN TREATED NAPHTHA - NAPHTHA (PETROLEUM), HYDROTREATED HEAVY

265-150-3	64742-48-9	-	Asp. Tox. 1: H304; Flam. Liq. 3: H226	<1%
-----------	------------	---	---------------------------------------	-----

[cont...]

# SAFETY DATA SHEET

POLYESTER EASY SAND PRIMER/ POLYESTER HIGH  
BUILD BASE PRIMER/ FOUNDATION PRIMER

Page: 3

LOW BOILING POINT NAPHTHA - UNSPECIFIED - SOLVENT NAPHTHA (PETROLEUM), LIGHT AROM.

265-199-0	64742-95-6	-	Asp. Tox. 1: H304; Flam. Liq. 3: H226; STOT SE 3: H335; Aquatic Chronic 2: H411	<1%
-----------	------------	---	---	-----

## Section 4: First aid measures

### 4.1. Description of first aid measures

**Skin contact:** Drench the affected skin with running water for 10 minutes or longer if substance is still on skin.

**Eye contact:** Bathe the eye with running water for 15 minutes. Consult a doctor.

**Ingestion:** Wash out mouth with water. Consult a doctor.

**Inhalation:** Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

### 4.2. Most important symptoms and effects, both acute and delayed

**Skin contact:** No data available.

**Eye contact:** No data available.

**Ingestion:** No data available.

**Inhalation:** No data available.

**Delayed / immediate effects:** No data available.

### 4.3. Indication of any immediate medical attention and special treatment needed

## Section 5: Fire-fighting measures

### 5.1. Extinguishing media

**Extinguishing media:** Alcohol or polymer foam. Carbon dioxide. Dry chemical powder. Use water spray to cool containers.

### 5.2. Special hazards arising from the substance or mixture

**Exposure hazards:** Highly flammable. In combustion emits toxic fumes. Vapour may travel considerable distance to source of ignition and flash back.

### 5.3. Advice for fire-fighters

**Advice for fire-fighters:** Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

## Section 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

**Personal precautions:** Refer to section 8 of SDS for personal protection details. If outside do not approach from downwind. If outside keep bystanders upwind and away from danger point. Turn leaking containers leak-side up to prevent the escape of liquid. Eliminate all sources of ignition.

[cont...]

# SAFETY DATA SHEET

POLYESTER EASY SAND PRIMER/ POLYESTER HIGH  
BUILD BASE PRIMER/ FOUNDATION PRIMER

Page: 4

## 6.2. Environmental precautions

**Environmental precautions:** Do not discharge into drains or rivers. Contain the spillage using bunding.

## 6.3. Methods and material for containment and cleaning up

**Clean-up procedures:** Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method. Do not use equipment in clean-up procedure which may produce sparks.

## 6.4. Reference to other sections

**Reference to other sections:** Refer to section 8 of SDS.

## Section 7: Handling and storage

### 7.1. Precautions for safe handling

**Handling requirements:** Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Avoid the formation or spread of mists in the air. Smoking is forbidden. Use non-sparking tools.

### 7.2. Conditions for safe storage, including any incompatibilities

**Storage conditions:** Store in a cool, well ventilated area. Keep container tightly closed. Keep away from sources of ignition. Prevent the build up of electrostatic charge in the immediate area. Ensure lighting and electrical equipment are not a source of ignition.

### 7.3. Specific end use(s)

**Specific end use(s):** No data available.

## Section 8: Exposure controls/personal protection

### 8.1. Control parameters

**Hazardous ingredients:**

#### STYRENE

**Workplace exposure limits:**

**Respirable dust**

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	430 mg/m <sup>3</sup>	1080 mg/m <sup>3</sup>	-	-

#### ETHYL ACETATE

UK	200 ppm	400 ppm	-	-
----	---------	---------	---	---

#### ACETONE

UK	1210 mg/m <sup>3</sup>	3620 mg/m <sup>3</sup>	-	-
----	------------------------	------------------------	---	---

### DNEL/PNEC Values

**DNEL / PNEC** No data available.

[cont...]

# SAFETY DATA SHEET

POLYESTER EASY SAND PRIMER/ POLYESTER HIGH  
BUILD BASE PRIMER/ FOUNDATION PRIMER

Page: 5

## 8.2. Exposure controls

**Engineering measures:** Ensure there is sufficient ventilation of the area. Ensure lighting and electrical equipment are not a source of ignition.

**Hand protection:** Protective gloves.

**Eye protection:** Safety glasses. Ensure eye bath is to hand.

**Skin protection:** Protective clothing.

## Section 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

**State:** Liquid

**Colour:** Various

**Odour:** Characteristic odour

**Viscosity:** Viscous

**Flash point°C:** <21

### 9.2. Other information

**Other information:** No data available.

## Section 10: Stability and reactivity

### 10.1. Reactivity

**Reactivity:** Stable under recommended transport or storage conditions.

### 10.2. Chemical stability

**Chemical stability:** Stable under normal conditions. Stable at room temperature.

### 10.3. Possibility of hazardous reactions

**Hazardous reactions:** Hazardous reactions will not occur under normal transport or storage conditions.  
Decomposition may occur on exposure to conditions or materials listed below.

### 10.4. Conditions to avoid

**Conditions to avoid:** Heat. Hot surfaces. Sources of ignition. Flames.

### 10.5. Incompatible materials

**Materials to avoid:** Strong oxidising agents. Strong acids.

### 10.6. Hazardous decomposition products

**Haz. decomp. products:** In combustion emits toxic fumes.

## Section 11: Toxicological information

### 11.1. Information on toxicological effects

[cont...]

# SAFETY DATA SHEET

POLYESTER EASY SAND PRIMER/ POLYESTER HIGH  
BUILD BASE PRIMER/ FOUNDATION PRIMER

Page: 6

## Hazardous ingredients:

### STYRENE

IVN	MUS	LD50	90	mg/kg
ORL	MUS	LD50	316	mg/kg
ORL	RAT	LD50	2650	mg/kg

### ETHYL ACETATE

ORL	MUS	LD50	4100	mg/kg
ORL	RAT	LD50	5620	mg/kg
SCU	RAT	LDLO	5	gm/kg

### ACETONE

IVN	RAT	LD50	5500	mg/kg
ORL	MUS	LD50	3000	mg/kg
ORL	RAT	LD50	5800	mg/kg

### LOW BOILING POINT NAPHTHA - UNSPECIFIED - SOLVENT NAPHTHA (PETROLEUM), LIGHT AROM.

ORL	RAT	LD50	8400	mg/kg
-----	-----	------	------	-------

## Relevant hazards for substance:

Hazard	Route	Basis
Skin corrosion/irritation	DRM	Hazardous: calculated
Serious eye damage/irritation	OPT	Hazardous: calculated
Reproductive toxicity	--	Hazardous: calculated
STOT-repeated exposure	-	Hazardous: calculated

## Symptoms / routes of exposure

**Skin contact:** No data available.

**Eye contact:** No data available.

**Ingestion:** No data available.

**Inhalation:** No data available.

**Delayed / immediate effects:** No data available.

## Section 12: Ecological information

### 12.1. Toxicity

[cont...]

# SAFETY DATA SHEET

POLYESTER EASY SAND PRIMER/ POLYESTER HIGH  
BUILD BASE PRIMER/ FOUNDATION PRIMER

Page: 7

## Hazardous ingredients:

### ACETONE

BLUEGILL ( <i>Lepomis macrochirus</i> )	LC50	8300	mg/l
---	------	------	------

## 12.2. Persistence and degradability

**Persistence and degradability:** No data available.

## 12.3. Bioaccumulative potential

**Bioaccumulative potential:** No data available.

## 12.4. Mobility in soil

**Mobility:** No data available.

## 12.5. Results of PBT and vPvB assessment

**PBT identification:** This product is not identified as a PBT/vPvB substance.

## 12.6. Other adverse effects

**Other adverse effects:** No data available.

## Section 13: Disposal considerations

### 13.1. Waste treatment methods

**Disposal operations:** Transfer to a suitable container and arrange for collection by specialised disposal company.

**NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

## Section 14: Transport information

### 14.1. UN number

**UN number:** UN1263

### 14.2. UN proper shipping name

**Shipping name:** PAINT RELATED MATERIAL

### 14.3. Transport hazard class(es)

**Transport class:** 3

### 14.4. Packing group

**Packing group:** II

### 14.5. Environmental hazards

**Environmentally hazardous:** No

**Marine pollutant:** No

[cont...]

# SAFETY DATA SHEET

POLYESTER EASY SAND PRIMER/ POLYESTER HIGH  
BUILD BASE PRIMER/ FOUNDATION PRIMER

Page: 8

## 14.6. Special precautions for user

**Special precautions:** No special precautions.

**Tunnel code:** D/E

**Transport category:** 2

## Section 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

**Specific regulations:** Not applicable.

### 15.2. Chemical Safety Assessment

## Section 16: Other information

### Other information

**Other information:** This safety data sheet is prepared in accordance with Commission Regulation (EU) No 453/2010.

**Phrases used in s.2 and s.3:** EUH066: Repeated exposure may cause skin dryness or cracking.

EUH208: Contains <name of sensitising substance>. May produce an allergic reaction.

H225: Highly flammable liquid and vapour.

H226: Flammable liquid and vapour.

H304: May be fatal if swallowed and enters airways.

H315: Causes skin irritation.

H319: Causes serious eye irritation.

H332: Harmful if inhaled.

H335: May cause respiratory irritation.

H336: May cause drowsiness or dizziness.

H361d: Suspected of damaging the unborn child.

H372: Causes damage to organs <or state all organs affected, if known> through prolonged or repeated exposure <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>.

H411: Toxic to aquatic life with long lasting effects.

**Legal disclaimer:** The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.